

Ottawa County Remonumentation  
**LAND CORNER RECORDATION CERTIFICATE**  
 Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED

93 DEC 15 AM 9:30

*Richard Robinson*  
 REGISTER OF DEEDS  
 OTTAWA COUNTY, MI

For corners in

<u>Ottawa</u> (County)	Located In:	Corner Code #
	<u>Robinson Township</u>	
1. Public Land Survey	T <u>7N</u> R <u>15W</u>	<u>G-7</u>
	T _____ R _____	<u>SE Corner</u>
	T _____ R _____	<u>Section 16</u>
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
 5. Private Claims \_\_\_\_\_

**Carl P. Englert Jr.**

I, \_\_\_\_\_, in a field survey on November 10, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

A. Description of original monument and accessories and/or subsequent restoration:  
 G-7

L.C.R.C., liber 3, Page 181, (9-16-1977)  
 Fd. 1/2" rod in monument box  
 SE, P.K. in guy pole 57.46'  
 NE, Centerline of stop sign 52.00'  
 NW, Nail in face of P.P. 57.10'  
 SW, 14" Oak 101.83'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-7  
 Found 3" Harrison in monument box and accepted as a careful and faithful perpetuation of the position of the original corner.  
 SW 14" Oak 101.83'  
 NW nail in face of P.P. 57.10'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-7  
 3" Harrison cast iron monument in monument box  
 O.C. Remon. Tag & Nail in NE side P.P., N 62 degrees W 60.08'  
 O.C. Remon. Tag & Nail in NW side Litepole, N 49 degrees E 43.14'  
 O.C. Remon. Tag & Nail in SW side 18" Oak, S 44 degrees E 91.95'  
 O.C. Remon. Tag & Nail in W side P.P., S 25 degrees W 131.10'  
 O.C. Remon. Tag & Nail in NE side 15" Oak, S 59 degrees W 110.81'

(E.D.M.)

Signed by Carl P. Englert Jr.  
 Surveyor's Michigan License No. 18987

Date 12/6/93

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN 1987  
 REVISED 1987

