

1993

COMMISSION

OTTAWA COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED

93 DEC 16 PM 1:00

Deborah Williams
REGISTER OF DEEDS
OTTAWA COUNTY, MI

For corners in

Ottawa (County)	Located In:	Corner Code #
1. Public Land Survey	T 7N R 16W	H-11 N $\frac{1}{2}$ corner Section 34
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, THOMAS E. JOINER in a field survey on 8-27-93, 1993
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

$\frac{1}{2}$ " Iron Pipe	Cast Iron Monument	Liber 4, Pg. 13	7-18-79
	N.E. Twin 14" Maple	33.65	
	S.E. 12" Maple	29.60	
	S.W. 19" Beech	39.42	
	N. 8" Yellow	16.55	

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found cast iron monument and accepted as a careful and faithful perpetuation of the
position of the original corner.

N.E. Twin 14" Maple	33.65
S.E. 12" Maple	29.60
S.W. 19" Beech	39.42
N. 8" Birch	16.55



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Cast Iron Monument			
O.C. Remon tag & nail West Side	10" Red Pine	N. 05° E.	70.02
O.C. Remon tag & nail West Side	12" Maple	S. 45° E.	35.78
O.C. Remon tag & nail East Side	21" Beech	S. 15° W.	40.63
O.C. Remon tag & nail West Side	10" Twin Maple	N. 15° W.	82.27

Signed by Thomas E. Joiner Date 8-31-93
Surveyor's Michigan License No. 18435