Liber 4 Page 339

OTTAWA COUNTY REMONUMENTATION

99 SEP -9 PM 12: 15

OVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 REVISED MAY 14,1975 REVISED JAN., 1983 REVISED OCT., 1995

SECTIO	Filin	g Requirement of	RUATION CERT	IFICATE "	,	erite, i û
For corners in		g cradumonionicon	Not 74, WIICH, P.A	1. 1970	D. D.	0.00
Ottawa	Located In:	Corner Code #			REGISTER OF	<i>DEFOS</i>
(County)			-		OTTAYA COLA	MYM
1. Public Land Survey	T <u>8N</u> R_ T R_ T R_	14W K-2 (WW Polkton				
2. Property Controlling in Section3. Miscellaneous Property in Sec.	TR_ S TR_ S TR_ S TR_ S TR			Register of	Deeds Stamp &	k File Number
4. Lot No, Recor	ded Plat					
5. Private Claims				A B C D	E F G H	I J K L M
I, Donald W. Schiele requirements of P.A. 74, Michiga	, in a field survey on	Aug. 24, 19 99 d	o hereby state that und	2 6 5 3 der 4 7 8	9-10-	1 1 12
conformance with regulations and United States Department of the li- that the corner points mentioned Board of Land Surveyors or by recovered, found as expressed be	nterior, Bureau of Land Mai in lines 3, 4 and 5 above w a Decree of a Court of	in the current manual of a nagement or by a decree	survey instructions of t of a Court of Law and	the 5 18 17	16 15	1413-
NOTE: Not more than 2 com		and range, may be rec	orded	8 19 20	2122-	23 24
co, una columbia.				10 30 29	28 27	26 25
A. Description of original mor K-2 1/4 corner comm Original Government Beech 8 qr section c 8" Beech W Ash 22 S40W 13 John Mullett, Deputy April 9, 1837	on to Sections Corner Record: orner	1 & 2, Polkton L.C.R C.P. <u>K-2</u>	TwpC. recorded Englert, Jr. (Found) 1/2" N.W. 55.28 W. 27.62 E. F.P. 30	Rod 12" Butternut 14" Butternut	(SEE R	OY REVERSE)
B. Description of corner evide K-2 Found Cast Iron surface of aspha- of the original Centerline Fence Post	молимент inscri ilt road, and ac corner.	cepted as a co	unty Section	Corpor! in Me	onument Box wation of t	, 9" below he position
·			73	********* ∑	130A	7
C. Description of monument to K-2 Cast Iron Monume surface of aspha	nt inscribed "U It road.	ttawa County S	ection Corne	position of the corner: r" in Monument	Box', 9" be	elow
Set Ottawa County Rem Set Ottawa County Rem Set Ottawa County Rem Set Ottawa County Rem Centerline North & So On fence remnant line On fence line ± to We	on lag & nail i on Tag & nail i on Tag & nail i uth asphalt roa ± to East.	n South side o n East side of n North side o	f 18" Elm Triple 7" Ma	S	88°30'E 4 S13°W 18	16.10 '(E) 15.00 PHOTO 15.36 FG CUNNER 19.05 PHOTO 19.05 PHOTO 15.00 PHOTO 15.00 PHOTO 15.00 PHOTO 15.00 PHOTO 15.00 PHOTO
Signed by Description Surveyor's Michigan License No.	23517	Donald W	Date	August 25, 19		
_	· 4	Schlele	₹ ★ %			

Part A., continued:

L.C.R.C. recorded in L.3, P.236, 12-21-77 by Thomas E. Joiner:

K-2) Replaced 1/2" Iron with Cast Iron Monument inscribed "Ottawa County Section Corner."

Ties: CL of Fence Post Tack in Hub 53.91 W SW 45.79 West Edge of 1%" Iron Pipe (Fence Corner) Ε 50.941

FEB 2 4 2000

SECTION

