RECORDED

OTTAWA COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74. Mich. P.A. 1970

96 0EC 18 PM 4: 55

For corners in	ւ ուսն vedan	rement of Act 74, Mile	on. P.A. 1970	Polyecki C	and discussion
Ottawa (County)	Located In: Cor Crockery Towns	nerCode# hip		REGISTER O	F DEEDS UNTY, MI
1. Public Land Survey	T <u>8NR 15W</u> TR TR TR	$\frac{\frac{M-12}{E \text{ $\frac{1}{4}$ corner}}}{\frac{\text{Section}}{\text{Section}}} 36$			
Property Controlling in Section Miscellaneous Property in Sec.	S T R S T R S T R S T R		Regi	ister of Deeds Stamp	& File Number
4. Lot No, Record	led Plat		- A B	CDEFGH	I J K L M
conformance with regulations and r United States Department of the In that the corner points mentioned in	in a field survey on 9/3 P.A. of 1970, the corner points me ules therefore as required in the curreterior, Bureau of Land Management in lines 3, 4 and 5 above were in con a Decree of a Court of Law; estaw:	entioned in lines 1 and 2 ab rent manual of survey instru- or by a decree of a Court of formance with the rules of the	ctions of the Law and /or 6 -18-	8 9 10 10 10 10 10 10 10 10 10 10 10 10 10	
NOTE: Not more than 2 corne on this certificate.	ers, all in the same town and rang	e, may be recorded	9 10—30- 11 12—31-	29 28 27 33 33 34 36	35 36
A. Description of original mon			13		
Set 1/4 Secti W. Oak 12"	common to Section 1837 by John Mull on Post from which dia. bears S720W dia. bears N520 See other	lett ch a 25 links PW 7 links	15W & Sectio LCRC Liber Found 1/2" S. 36" Map1 N.E. 16" Pi E. P.P. 88. S.W. P.P. 9	1, Page 637 rod e 88.82' ne 45.52'	R14W Sept. 1972
B. Description of corner evide	ence found and/or method appli	ied in restoring or reestal	blishing corner:		
M-12 1/4 corner Found Cast Ir Found P.P. S. Found 16" Pin	common to Section Monument W. 92.40' e N.E. 45.52'	_	15W & Section	M5 OTTAWA CO	CUNTY
Found P.P. Ea	st 88.93'		PEER APPR	ROVED 12 -	7 76
Accepted as a position of	careful and fait the corner	chful perpetua	ntion of the	original .	
C. Description of monument fo	or corner and accessories estab	lished to perpetuate loca	ating the position of the	e corner;	-
O.C. Remon Tagor C.C.	common to Section ast Iron Monument g & Nail in E. Sing & Nail in S. Sing & Nail in W. Sing & Nail in N.E.	; - Placed Mor de P.P. de P.P. de 16" Pine	nument Box S49°W 92.6° N84°E 89.0°	7 ' 1 ' 5 '	R14W
Signed by <u>Au</u> Surveyor's Michigan License No	Engleit		De cam.	PROFESSION SUPVEYOR 18987	OPN HOUSE
		FORM APPROV	/ED BY MICHIGAN STATE BO	ARD OF PROFESSIONAL SUF	IVEYORS, JAN. 28, 1971 REVISED MAY 14,1975 REVISED JAN., 1983
	р емок	I I TRED 3 DACE 3	5.0		REVISED OCT., 1995

 $^{M-12}$ 1/4 corner common to Section 36, T8N, R15W and Section 31, T8N, R14W

LCRC Liber 2, Page 75 March 1973 Found Steel Bar at 96th & Leonard P.P. S.W. 92.40' 16" Pine N.E. 44.75' St. Sign S.E. 50.20' T. Pole N.N.E. 43.38'