

RECORDED

93 DEC 16 PM 1:01

OTTAWA COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE

COULFORD

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Ottawa (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>8N</u> R <u>16W</u>	L-9, S $\frac{1}{4}$ Corner Section 24
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

D. J. ...
REGISTER OF DEEDS
OTTAWA COUNTY, MI

Register of Deeds Stamp & File Number

- 4. Lot No. _____, Recorded Plat _____
- 5. Private Claims _____

I, THOMAS E. JOINER in a field survey on 11-3-, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Found 3/4" Pipe In Monument Box	Set Cast Iron Monument
Powerpole S.W. 54.48	Liber 5, Pg. 93
Powerpole S.E. 37.63	Tele. Pole N.E. 45.32
Tele. Pole N.E. 44.86	Hydrant N.E. 62.62
	Light Pole S.W. 37.68
	Powerpole S.W. 54.32

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found cast iron monument and accepted as a careful and faithful perpetuation of the position of the original corner.

Powerpole	S.W.	54.32
Hydrant	N.E.	62.62
Tele. Pole	N.E.	45.32



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Cast Iron Monument In Box

O.C. Remon tag & nail in West face powerpole	AZ. 45° 21' 30"	45.46
O.C. Remon tag & nail in Bike Path	AZ. 316° 43' 43"	41.92
O.C. Remon tag & nail in S.E. face powerpole	AZ. 228° 01' 10"	54.23
O.C. Remon tag & nail in West face powerpole	AZ. 138° 35' 33"	37.35

Signed by Thomas E. Joiner
Surveyor's Michigan License No. 18435

Date 11-19-93