## SURVEY & REMONUMENTATION

NOV 1 0 1993

CO	A A	AAI	606	100	٨
8 7 8	1 M i	114	D 40 -	f may	· 7

## LAND CORNER RECORDATION CERTIFICATE

Filing	Requirement	of Act	74,	Mich.	P.A.	1970

RECORDED

1. Public Land Servey  T. M. 134  T. N. M.	OTTAWA (County)	OTTAWA COL Located In:	JNTY REMONU Corner Cod	l l	N 1993	SEP 29	PM 3: 14	
2. Property Controlling S T R  1. Randal D. Esenstra in a fleid survey on	1. Public Land Survey	T <u>9N</u> R <u>13W</u> TR	(K-6)E ½ Co	or-14				na.
1. Randal D. Feenstra in a field survey on July 20  do hereby certify that under requirements of P.A.74.Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 show were in conformance with repulsions and rules therefore as required in the current instance of survey instructions of the thirde Steel becomered in the instance. Survey is used of and Management or by a decree of a Court of Lew and/or that the corner points mentioned in lines 1 and 2 shows were in conformance with the rose of the Michigan Stear of Advisory of the Court of Lew and/or that the corner points mentioned in lines 3, 4 and 5 an	in Section S  3. Miscellaneous S	T R T R T R			Registe	er of Deed	s Stamp & F	ile Number
I. Randal. D. Evenstra in a field survey on July 20  19 93  do haveby cardly that under requirements of P.A. 74. Michigan P.A. of 1870. In accorate points mentioned in lines 1 and 2 above were in conformance with reputations and rules therefore as required in the current manual of survey instructions of the United States Department of the Intensio, Bureau of Land Management of ya decree of a Court of Law and/or that the corner points mentioned in lines 1,4 and 5 above were in conformance with the rules of the Michigan Board of Land Survey into rot by a bactree of a court of Law additional time corner points mentioned in lines 1,4 and 5 above were in conformance with the rules of the Michigan Board of Land Survey into rot by a bactree of a court of Law additional time to corner points mentioned in lines 1,4 and 5 above were in conformance with the rules of the Michigan Board of Land Survey into rot by a bactree of a court of Law additional time to Land Survey in the Michigan Board of Land Survey In the Michigan Board Survey In					<del></del>	A B C	DEFG	H 1 J K L
Found Cast Iron Monument in Box And Witnesses Ger 200  C. Description of monument for comer and accessories established to perpetuate localing the position of the corner:  - K-5-Cast Iron Monument per L-4, P-233, Ottawa County, MI, and is accepted as a careful and O.C. Remon. Nail & Tag in Power Pole  "X" in North end culvert  "X" in South end culvert  "X" in South end culvert  "C. Remon. Nail & Tag in Fence Post  "X" in South end culvert  "C. Remon. Nail & Tag in Fence Post  "X" in South end culvert  "C. Remon. Nail & Tag in Fence Post  "X" in South end culvert  "C. Remon. Nail & Tag in Fence Post  "X" in South end culvert  "X" in So	1, Randal D. Feenstra in a field do hereby certify that under requirements in lines 1 and 2 above were in conforms current manual of survey instructions of Management or by a decree of a Court of Law; established, re-established re-established expressed below:  NOTE: Not more than 4 corners, a on this certificate.  A. Description of original monumer K-5 = LCRC#'s L-3, P-254	d survey on July 20 s of P.A. 74, Michigan P.A. of ance with regulations and the United States Department and or that the corner is of the Michigan Board of the dichigan Board of the monumented, re-monumented, re-monument and accessories and/1; L-4, P-233	0 11970, the corne rules therefore nent of the Interi- points mentioned Land Surveyors onumented, rec	, 19 <u>93</u> rpoints mentic as required in or, Bureau of L d in lines 3, 4 a or by a Decree overed, found	3 4 5 5 6 6 1 the 2 7 6 6 7 6 7 6 7 7 7 7 7 7 7 7 7 7 7 7	-13 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1	3	3
C. Description of monument for comer and accessories established to perpetuate locating the position of the corner:  - K-5-Cast Iron Monument per L-4, P-233, Ottawa County, MI, and is accepted as a careful and O.C. Remon. Nail & Tag in Power Pole  - X" in North end culvert  - X" in South end culvert  - X = CL Hoover-5'N  - K-6-Cast Iron Monument per L-6, P-109, Ottawa County, MI, and is accepted as a careful and O.C. Remon. Nail & Tag in Fence Post  - O.C. Remon. Nail & Tag in Fence Post  - O.C. Remon. Nail & Tag in Fence Post  - O.C. Remon. Nail & Tag in Fence Post  - O.C. Remon. Nail & Tag in Fence Post  - O.C. Remon. Nail & Tag in Fence Post  - O.C. Remon. Nail & Tag in Fence Post  - O.C. Remon. Nail & Tag in Power Pole  - O.C. Remon. Nail & Tag in Pow		iound and/or method ap		ing or reesta				₹ <b>7</b> 12.
C. Description of monument for comer and accessories established to perpetuate locating the position of the corner:  - K-5-Cast Iron Monument per L-4, P-233, Ottawa County, MI, and is accepted as a careful and O.C. Remon. Nail & Tag in Power Pole S60°W 106.83 faithful perpetuation of the "X" in North end culvert N55°E 53.61 position of the original corner. "X" in South end culvert S60°E 53.78  O.C. Remon. Nail & Tag in Fence Post N40°W 75.74  CL 8th, Cl Hoover-5'N  - K-6-Cast Iron Monument per L-6, P-109, Ottawa County, MI, and is accepted as a careful and O.C. Remon. Nail & Tag in Fence Post S40°W 67.97 faithful perpetuation of the O.C. Remon. Nail & Tag in Fence Post N60°W 50.08 position of the original corner. O.C. Remon. Nail & Tag in Power Pole N10°W 159.33  O.C. Remon. Nail & Tag in Power Pole N10°W 159.33  O.C. Remon. Nail & Tag in Power Pole N90°E 166.86  CL 8th  Signed by Auxilia O. Technical Date July 20, 1993	And Witnesses Ger -288	t in Box	And Witn	esses Per	Monument S.j.)	***************************************	RANDAL D. FEENSTRA LAND SURVEYOR NO. 37275	*****
- K-5-Cast Iron Monument per L-4, P-233, Ottawa County, MI, and is accepted as a careful and O.C. Remon. Nail & Tag in Power Pole S60°W 106.83 faithful perpetuation of the "X" in North end culvert N55°E 53.61 position of the original corner. "X" in South end culvert S60°E 53.78 O.C. Remon. Nail & Tag in Fence Post N40°W 75.74  OCL 8th, Cl. Hoover-5'N  - K-6-Cast Iron Monument per L-6, P-109, Ottawa County, MI, and is accepted as a careful and O.C. Remon. Nail & Tag in Fence Post S40°W 67.97 faithful perpetuation of the O.C. Remon. Nail & Tag in Fence Post N60°W 50.08 position of the original corner. O.C. Remon. Nail & Tag in Power Pole N10°W 159.33 O.C. Remon. Nail & Tag in Power Pole N90°E 166.86  OCL 8th  Signed by Auxilia Occupant Date July 20, 1993								
0.C. Remon. Nail & Tag in Fence Post N60°W 50.08 position of the original corner.  0.C. Remon. Nail & Tag in Power Pole N10°W 159.33  0.C. Remon. Nail & Tag in Power Pole N90°E 166.86  © CL 8th  Signed by Karrale Description of the original corner.  Date July 20, 1993	- K-5-Cast Iron Monument O.C. Remon. Nail & Tag "X" in North end culver "X" in South end culver O.C. Remon. Nail & Tag  OCL 8th, - K-6-Cast Iron Monument	per L-4, P-233, C in Power Pole t t in Fence Post CL Hoover-5 per L-6, P-109, C	Ottawa Cour S60°W N55°E S60°E N40°W 'N Ottawa Cour	ty, MI, a 106.83 53.61 53.78 75.74	and is ac faithful position and is ac	ccepted perpetu of the ccepted	as a care nation of original as a care	the corner. eful and
Signed by Randel Steeristic Date July 20, 1993	O.C. Remon. Nail & Tag O.C. Remon. Nail & Tag O.C. Remon. Nail & Tag	in Fence Post in Power Pcle	N60°W	50.08 ( 159.33 166.86	position	of the	original	
		S. Treus	tre	Date	Sulef	20,	1443	