

SURVEY & REMONUMENTATION

APR 29 1996

JUDITH D. ROEHM
Ontonagon County
LC 3/319 JEM Feet: 9.00
09/25/95
14:43
Page 1 of 1

COMMISSION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

<u>Ontonagon</u> <small>(County)</small>	Located In:	Corner Code #	
1. Public Land Survey	T 49N. R 42W.	G-2	
	T _____ R _____	_____	
	T _____ R _____	_____	
	T _____ R _____	_____	
2. Property Controlling in Section	S _____ T _____ R _____	_____	
	S _____ T _____ R _____	_____	
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____	
	S _____ T _____ R _____	_____	

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

1/4 corner 3 & 4; T.49 N., R.42 W.

I, Richard L. Drahn, in a field survey on August 22, 19 95
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by William Burt on June 12, 1848. Original B.T.s
---Y. Birch 18" West 7 links (4.62') --- Hemlock 18" N.87 E., 30 links
(19.80')

Corner restored by Richard L. Drahn, R.L.S. 21564 on 8/24/77 from the remains of the original B.T.s and from natural features and distances to recovered corners north and south. He set a 2" by 5' galvanized iron pipe with a 3" stamped brass cap and the following new B.T.s; --- 9" (11") Sugar Maple N.27W. (N.26 W.) 29.2' (29.42') --- 8" (10") Sugar Maple S.30 E. (S.27 E.) 30.4' (30.49') --- 12" (14") Sugar Maple S.61 W. (S.64 W.) 31.8' (31.83') --- 7' Metal sign

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

post South (S.01 W.) 2.0' (1.94') Recorded in Liber 1, Page 160 on 4/25/79 in Ontonagon County.

Recovered monument as described and bearing trees as shown in parentheses above. Fragments of hemlock wood and bark still remain from the original hemlock bearing tree.

Act 74 research form of file with Ontonagon County Records.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

New bearing tree established:

14" Sugar Maple N.48 E. 25.72'

PEER GROUP APPROVED

Earl Anshelkamp 9-20-95
COUNTY REPRESENTATIVE



Signed by Richard L. Drahn Date September 10, 1995

Surveyor's Michigan License No. 21564