

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

ONTONAGON Co.

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY	T. <u>51N</u> N. S., R. <u>37W</u> E. W.	D12	REGISTER OF DEEDS STAMP AND FILING NUMBER
2. PROPERTY CONTROLLING IN SECTION	<u>35</u> T. <u>51N</u> N. S., R. <u>37W</u> E. W.	14	
3. MISCELLANEOUS PROPERTY IN SECTION	T. _____ N. S., R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____			
5. PRIVATE CLAIMS _____			

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on May 25, 1979, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner 14: Not set on original survey nor subsequently apparently.

Corner D12: Not set on original survey. Found old post at approximate center of section.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner 14: Established on line and midway between corners.

Corner D12: Established at intersection of north-south and east-west 1/4 lines.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner 14: Set 1" I.D. x 36" iron pipe with 4" aluminum cap.
 5" Maple N80°E 28.9 Ft. 1/16 S, BT
 5" Maple S71°E 29.7 Ft. 1/16 S, BT

Corner D12: Set 1" I.D. x 36" iron pipe with 4" aluminum cap.
 9" Maple S45°W 25.4 Ft. 1/4 S, BT
 11" Hemlock S17°E 10.5 Ft. 1/4 S, BT
 5" Balsam N08°E 13.6 Ft. 1/4 S, BT

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE 2/6/80
CHIEF OF SURVEY PARTY
 MICHIGAN REGISTERED LAND SURVEYOR
 Keith L. Sackett
 Michigan Dept. of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

