

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY.....	T. 51 N. S. R. 40 W.	J-13, L-11
2. PROPERTY CONTROLLING IN SECTION.....	T. _____ N. S., R. _____ E. W.	_____
3. MISCELLANEOUS PROPERTY IN SECTION.....	T. _____ N. S., R. _____ E. W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Jackett do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970 the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were in a field survey on see below 19\_\_\_\_, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_ 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

**A. Description of original monument and accessories and/or subsequent restoration:**

Corner J-13: Original monument and accessories not found.  
Corner L-11: Original monument and accessories not found.

**B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:**

Corner J-13: Re-established 1-13-77 on line between section corners.  
 Corner falls in beaver pond.  
Corner L-11: Re-established 1-19-77 on line between section corners.

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner**

Corner J-13: Set 1" O.D. by 4 foot iron pipe in beaver pond.  
 5" Ash N25°W 47.4 ft. 1/4 S, NBT  
 4" Maple S74°W 56.2 ft. 1/4 S, NBT  
Corner L-11: Set 1" I.D. by 1/2" iron pipe.  
 6" Maple N34°E 8.7 ft. 1/4 S, NBT  
 7" Maple N43°W 20.9 ft. 1/4 S, NBT  
 7" Maple S76°W 20.0 ft. 1/4 S, NBT

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR  
 Keith L. Jackett

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

