

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

ONTONAGON CO

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>53N</u> N. S., R. <u>37W</u> E. W.	<u>F7, F6</u>
2. PROPERTY CONTROLLING IN SECTION _____	T. _____ N. S., R. _____ E. W.	_____
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. S., R. _____ E. W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on see below, 19____, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner F7: Original monument and accessories not found. Found old post and scribed trees by unknown person.

Corner F6: Not set on original survey nor subsequently apparently.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner F7: Restored 6-26-79 at post. Fits good with other corners and land calls.

Corner F6: Established 10-31-79 at calculated center 1/4 corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner F7: Set 1" I.D. x 36" iron pipe with 4" aluminum cap.
 18" Cedar N40°E 13.3 Ft. 1/4 S, NBT
 24" Cedar S07°W 23.3 Ft. 1/4 S, NBT

Corner F6: Set 1" I.D. x 36" iron pipe with 4" aluminum cap.
 8" Maple N70°E 12.0 Ft. 1/4 S, BT
 8" Maple S42°W 13.4 Ft. 1/4 S, BT
 5" Ash N16°W 15.6 Ft. 1/4 S, BT

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE 2/4/80

CHIEF OF SURVEY PARTY
 MICHIGAN REGISTERED LAND SURVEYOR

Keith L. Sackett
 Michigan Dept. of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

