

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

ONTONAGON Co.

FOR CORNERS OF—	LOCATED IN—	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. <u>53N</u> N. S., R. <u>37W</u> E. W.	<u>G6, G7</u>
2. PROPERTY CONTROLLING IN SECTION	T. _____ N. S., R. _____ E. W.	_____
3. MISCELLANEOUS PROPERTY IN SECTION	T. _____ N. S., R. _____ E. W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on June 28, 1979, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner G6: Original monument and accessories not found. Found old scribed post by M.C. Larsen set from original B.T. Found Forest Service Location Poster on 12" Y. Birch, N86°E, 19.6 Ft.

Corner G7: Original monument and accessories not found. Found old scribed post which fits good with other corners in area.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner G6: Restored at post.

Corner G7: Restored at post.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner G6: Set 1" I.D. x 36" iron pipe with 4" aluminum cap.
 4" Sugar S42°W 8.3 Ft. 1/4 S, NBT
 10" Sugar S74°E 27.1 Ft. 1/4 S, NBT
 4" Sugar N05°E 11.0 Ft. 1/4 S, NBT

Corner G7: Set 1" I.D. x 36" iron pipe with 4" aluminum cap.
 12" Hemlock N36°E 19.7 Ft. S 15, NBT
 12" Y. Birch S14°E 31.8 Ft. S 22, NBT
 4" Sugar N20°W 7.8 Ft. S 16, NBT

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE 2/6/80
CHIEF OF SURVEY PARTY
 Keith L. Sackett
MICHIGAN REGISTERED LAND SURVEYOR
 Michigan Dept. of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

