

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

ONTONAGON CO.

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>53N</u> N. S., R. <u>37W</u> E. W.	<u>E9, G8</u>
2. PROPERTY CONTROLLING IN SECTION _____	, T. _____ N. S., R. _____ E. W.	_____
3. MISCELLANEOUS PROPERTY IN SECTION _____	, T. _____ N. S., R. _____ E. W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on see below, 19____, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

- A. Description of original monument and accessories and/or subsequent restoration:
- Corner E9: Original monument and accessories not found. Found 1" I.D. iron pipe set by M. C. Larsen from original bearing tree.
 - Corner G8: Original monument and accessories not found. Found 1-1/2" iron pipe set by M. C. Larsen from original bearing tree.

- B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:
- Corner E9: Restored 6-11-79 at Iron pipe.
 - Corner G8: Restored 6-27-79 at Iron pipe.

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
- Corner E9: 1" I.D. x unknown length iron pipe 3 ft. high.
 10" Sugar S36°W 18.4 Ft. S 29, NBT
 16" Sugar S30°E 14.6 Ft. S 28, NBT
 5" Sugar N52°W 11.8 Ft. S 20, NBT
 - Corner G8: 1-1/2" I.D. x unknown length iron pipe.
 6" Sugar N40°E 3.0 Ft. 1/4 S, NBT
 20" Hemlock S02°W 17.7 Ft. 1/4 S, NBT

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE 2/6/80

CHIEF OF SURVEY PARTY
Keith L. Sackett
MICHIGAN REGISTERED LAND SURVEYOR
 Keith L. Sackett
 Michigan Dept. of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

