LIBER 318 PAGE 624

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

PRESQUE ISLE COUNTY RECORDED

	Presque Isle (County)	Located In:	Corner Code =##	96 JUN -4 AM II: 25
1.	Public Land Survey	T <u>34NR 5E</u> T R T R T R	B-7	Jena M. Lamd- REGISTER OF DEEDS
2.	Property Controlling in Section			
3.	Miscellaneous Property in Sec.	S T R S T R		Register of Deeds Stamp & File Number
4.	Lot No, i	Recorded Plat		— ABCDEFGHIJKL
5.	Private Claims			2 6 5 4 3 2 1
	*			3 4 7 8 9 10 11 12
		e in a field survey on <u>Decemb</u>		
in	lines 1 and 2 above were i	equirements of P.A. 74, Michigan P.A. o in conformance with regulations and ructions of the United States Departn	the the	
Ma	anagement or by a decree of	f a Court of Law and/or that the corner with the rules of the Michigan Board of	points mentioned in lines 3, 4 and	1d5 8 19 20 21 22 23 24
	ourt of Law; established, pressed below:	re-established, monumented, re-m	onumented, recovered, found	as 10 30 29 28 27 26 25
NO	OTE: Not more than 4 of	corners, all in the same town and	d range, may be recorded	11

A. Description of original monument and accessories and/or subsequent restoration:

B-7July 29, 1977 Aug. 2, 1977 Survey recorded in Liber 218, Pg. 396 1856 LCRC Subdivision by Ronald R. Bischer LS#22428 Alfred Millerd Delmer E. Porter Porter's Survey P.C. LS #15410 Set 1/2" Rod & Cap #15410 at Deputy Surveyor Set Quarter Sec Post 1/2" Rod & Cap #15410 Rd. Int. 7/13/1977 S73°E 162.74' P. Pole S51° W 47.75' P. Pole Hemlock 24 N70W 16 Hemlock 18 S80E 8 S51°W 47.75' P. Pole S73° E 162.74' P. Pole

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

B-7 December 8, 1995 Norman J. Quaine LS #33984, Porter's Survey P.C. 1996 P.T. Co. State Remonumentation

on this certificate.

For corners in

Fd. 1/2" Rod & Cap #15410

S51°W 47.83' P. Pole

S73° E 162.85' P. Pole

A CONTINUED:

Survey Recorded Liber 302, Pg 745 By Ronald R. Bischer LS #22428 S 1/4 - 1/2" Rod

o.	Description of monument for corner and accessories es	stablished to perpetuate locating the position of the corne
Ψ.	Description of monathern for corner and accessines as	And the property of the proper

B-7Left 1/2" Rod & Cap #15410 N71°W 170.41' P. Pole S70°W 76.93' NE Cor House S51°W 47.83' P. Pole S73°E 162.85' P. Pole

*Witness tags & nails.

Ratified by Peer Group in accordance with P.A.

Porter's Survey	P.C.		
Signed by Noman	I Quau	ie in	نی_
Surveyor's Michigan License	No. <u>3390</u>	8f	. "

Date