

97 DEC 22 AM 9:55

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

<u>Presque Isle</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>34</u> R <u>5E</u>	<u>K-11</u>
	T <u>   </u> R <u>   </u>	<u>   </u>
	T <u>   </u> R <u>   </u>	<u>   </u>
	T <u>   </u> R <u>   </u>	<u>   </u>
2. Property Controlling in Section	S <u>   </u> T <u>   </u> R <u>   </u>	<u>   </u>
	S <u>   </u> T <u>   </u> R <u>   </u>	<u>   </u>
3. Miscellaneous Property in Sec.	S <u>   </u> T <u>   </u> R <u>   </u>	<u>   </u>
	S <u>   </u> T <u>   </u> R <u>   </u>	<u>   </u>

*Janet M. Lamb*  
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Ronald Bischer, in a field survey on Sept 10, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K-11

GLO Notes  
Alfred Millerd  
Set Post  
Beech 6" N40° E 14 Lks  
Cedar 10" S27° W 20 lks

1989 Norman Quaine #33984  
Set 1/2" rod and Cap #15410  
and three witnesses



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-11

Found 1/2" Rod and Cap #15410  
and three Quaine witnesses

SURVEY &  
REMONUMENTATION

JAN 14 1998

SECTION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-11

1/2" Rod and cap #15410

N80° W	28.52'	10" Spruce	Quaine Witness
S78° E	25.38'	6" W. Ash	Quaine Witness
N52° E	27.10'	10" Apple	Quaine Witness
S50° W	34.60'	5" Aspen	

Ratified by Peer Group  
in accordance with P.A. 345

Chairman *Norman J. Quaine*  
Date 10/30/97

Signed by *Ronald R. Bischer*  
Surveyor's Michigan License No. 22428

Date Oct. 8, 1997