

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 35 N. R. 4 E.	A-12; B-12; C-12
2. PROPERTY CONTROLLING IN SECTION 31	T. 35 N. R. 4 E.	8
3. MISCELLANEOUS PROPERTY IN SECTION	T. S. R. E. W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on May 1, 1980, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 12 Found corner as restored in previous survey by Marcus Schaaf in a Survey of T35NR3E.
- 12 Set at calculated intersection of true 1/4 lines per standard survey procedure.
- 12 Set by proportionate measurement between section corner.
- 8 Set by standard survey procedure for the subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-12	B-12	C-12
4" R. Pine S41°E 38.00'	Set 5/8" rod w/RLS cap	DNR Mon/Red top post
3" R. Pine N52°E 32.7'	18" R. Pine S17°E 11.0'	4" R. Pine S14°E 22.4'
Cedar Post East 10'	20" R. Pine S35°W 24.6'	3" R. Pine S82°W 35.9'
		10
		Set 5/8" Rod w/RLS Cap
		6" R. Pine N03°E 17.2'
		3" R. Pine S82°W 24.2'

SIGNED BY Kenneth J. Ostling

DATE 9/4/80


SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_  
CHIEF OF SURVEY PARTY

DATE \_\_\_\_\_

APPROVED AND SIGNED BY \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR



SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_