## LAND CORNER RECORDATION CERTIFICATE

Communication of the second of

4.18

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN-:	CORNER CODE	. HOMOEK	
1. PUBLIC LAND SURVEY	T. 35 N. R. 4		2;	
2. PROPERTY CONTROLL- ING IN SECTION—3	1 ,T. 35 N. 4	_ E: 8; 5		
3. MISCELLANEOUS PROPERTY IN SECTION—		ł		
4. LOT NO , RE	CORDED PLAT			
5. PRIVATE CLAIMS				
	•		AEC	GISTER OF DEEDS STAMP AND FILING NUMBER
I, KENNETH J. OSTL the corner points mentioned in re-established, monumented, re and rules therefore as required Bureau of Land Management of and 5 above were, in a field sur as expressed below and in confinence of a Court of law: C. CONTINUED:	lines 1 and 2 above were e-monumented, recovered in the current manual or by a decree of a court vey on	e, in a field survey on  l or restored as expresse of survey instructions of sorvey instructions of sorvey instructions of the Michigan State Box	AUGUST 6 d below and in a the United States at the corner poi ecovered, restored, ard of Registration	, 19_84, established, conformance with regulations. Department of the Interior, nts mentioned in lines 3, 4, established or re-established.
SET 5/8" ROD W/RLS CA 6" RED PINE N2°W		SET 578" ROD W/ 9" JACKPINE S		ı
3" RED PINE S64°W 2		5" JACKPINE S		
B. Description of corner evide B-12 - SET BY STANDAR TRUE 1/4 LINES POSITION.	D SURVEY PROCEI	DURE, AT THE CA	ALCULATED I	NTERSECTION OF THE
TRUE 1/4 LINES POSITION.  C-12 - SET BY PROPORT ABOUT 38' NORT  8 - SET BY STANDAR  C. Description of monument for the set of the se	D SURVEY PROCED CORNER RESET  IONATE MEASUREN H TO REFLECT NO D SURVEY PROCED OF COTHER and accessories P 27.21	DURE, AT THE CAT ABOUT 17' NOR MENT BETWEEN SEEW NE CORNER LODURE FOR THE SUBSTRUCTURE FOR THE SUBSTRUCTURE SET DNR MOTHER PINCEPT OF THE SUBSTRUCTURE SET DNR MOTHER SET DNR MOT	ALCULATED INTH TO REFLECTION CORNOCATION.  UBDIVISION  BDIVISION  Color of the posion	NTERSECTION OF THE ECT NEW E 1/4 ERS. CORNER RESET OF SECTIONS. OF SECTIONS. tion of the corner:
TRUE 1/4 LINES POSITION.  -12 - SET BY PROPORT ABOUT 38' NORT  8 - SET BY STANDAR  5 - SET BY STANDAR  C. Description of monument for the set of the set o	D SURVEY PROCED CORNER RESET  IONATE MEASUREN H TO REFLECT NO D SURVEY PROCED OF COTHER and accessories P 27.21	DURE, AT THE CAT ABOUT 17' NOR MENT BETWEEN SEEW NE CORNER LOOURE FOR THE SUBJECT OF THE SUBJECT	ALCULATED IN THE TO REFLECTION CORNOCATION.  UBDIVISION  UBDIVISION  E locating the posion  C-12  UNUMENT	NTERSECTION OF THE ECT NEW E 1/4 ERS. CORNER RESET OF SECTIONS. OF SECTIONS. tion of the corner:
SIGNED BY  SIGNED BY  SIGNED BY  STANDAR  STANDAR  SURVEYOR'S MICHIGAN RI  TRUE 1/4 LINES  POSITION.  POSITION.  SET BY PROPORT  ABOUT 38' NORT  B - SET BY STANDAR  C. Description of monument for the series of th	D SURVEY PROCEE CORNER RESET  IONATE MEASUREM H TO REFLECT NE D SURVEY PROCEE OF COTHER and accessories  P 27.21 40.01  EGISTRATION NO	DURE, AT THE CAT ABOUT 17' NOR MENT BETWEEN SEEW NE CORNER LOOURE FOR THE SUBSTRUCTURE FOR THE SUBSTRUCTURE SET DNR MON 1" RED PIN 3" RED PIN 7" RED PIN 1" RED PIN 1	ALCULATED IN THE TO REFLECTION CORNOCATION.  JEDIVISION  JEDIVISION  Le locating the position of the position	NTERSECTION OF THE ECT NEW E 1/4  ERS. CORNER RESET  OF SECTIONS.  OF SECTIONS.  tion of the corner:  61.0' 55.5' 24.9'  ENNETH  OSTLING LAND LAND LAND NO. 10068 10068
SIGNED BY	D SURVEY PROCEE CORNER RESET  IONATE MEASUREM H TO REFLECT NE D SURVEY PROCEE OF COTHER and accessories  P 27.2' 40.0'  CHIEF OF SURVEY PARTY	DURE, AT THE CAT ABOUT 17' NOR MENT BETWEEN SEEW NE CORNER LOOURE FOR THE SUBJECT OF THE SUBJECT	ALCULATED IN ALCULATED IN ATE	NTERSECTION OF THE ECT NEW E 1/4  ERS. CORNER RESET  OF SECTIONS.  OF SECTIONS.  tion of the corner:  61.0' 55.5' 24.9'  KENNETH OF ANCE OF AN
SIGNED BY  SIGNED BY  STANDAR  TRUE 1/4 LINES  POSITION.  POSITION.  SET BY PROPORT  ABOUT 38' NORT  B - SET BY STANDAR  C. Description of monument for STATE AND UNITED STATE  SURVEYOR'S MICHIGAN RI  FOR STATE AND UNITED STATE  TO STATE AND UNITED STATE  TO STATE AND UNITED STATE  SURVEYOR'S MICHIGAN RI  SURVEYOR'S MICHIGAN RI  FOR STATE AND UNITED STATE  SURVEYOR'S MICHIGAN RI  SURVEYOR	D SURVEY PROCEE CORNER RESET  IONATE MEASUREM H TO REFLECT NE D SURVEY PROCEE OF COTHER and accessories  P 27.2' 40.0'  CHIEF OF SURVEY PARTY	DURE, AT THE CAT ABOUT 17' NOR MENT BETWEEN SEEW NE CORNER LOOURE FOR THE SUBJECT OF THE SUBJECT	ALCULATED IN ALCULATED IN ATE	NTERSECTION OF THE ECT NEW E 1/4  ERS. CORNER RESET  OF SECTIONS.  OF SECTIONS.  tion of the corner:  61.0' 55.5' 24.9'  KENNETH OSTLING LAND LAND LAND NO. 10068
SIGNED BY	D SURVEY PROCEE CORNER RESET  IONATE MEASUREM H TO REFLECT NE D SURVEY PROCEE OF COTHER and accessories  P 27.2' 40.0'  CHIEF OF SURVEY PARTY	DURE, AT THE CAT ABOUT 17' NOR MENT BETWEEN SEEW NE CORNER LOOURE FOR THE SUBJECT OF THE SUBJECT	ALCULATED IN ATE DATE DATE DATE	NTERSECTION OF THE ECT NEW E 1/4  ERS. CORNER RESET  OF SECTIONS.  OF SECTIONS.  tion of the corner:  61.0' 55.5' 24.9'  ENNETH  LAND LAND SURVEYOR NO. 10068

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET