

2000 PRESQUE ISLE COUNTY REMONUMENTATION

FEB 12 2001

**LAND CORNER RECORDATION CERTIFICATE**  
Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

For corners in

<u>Presque Isle</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>35</u> N R <u>2</u> E	<u>M-2</u>
	T ___ R ___	_____
	T ___ R ___	_____
	T ___ R ___	_____
2. Property Controlling in Section	S ___ T ___ R ___	_____
	S ___ T ___ R ___	_____
3. Miscellaneous Property in Sec.	S ___ T ___ R ___	_____
	S ___ T ___ R ___	_____

PRESQUE ISLE COUNTY  
RECORDED

2000 DEC 11 AM 9:54

*Jan M. Jamb*  
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Ronald Bischer, in a field survey on 10/24/00 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.


1	A	B	C	D	E	F	G	H	I	J	K	L	M
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

June 1840 John Hodgson set wood post and 2 witnesses  
August 1855 George Cannon set wood post  
Aug. 1999 Ronald Bischer #22428 set 1/2" rod and cap by single proportion using George Cannon's proportion left 4 new witnesses

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

found 1/2" rod and cap #22428 and 4 old witnesses



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Oct. 24, 2000  
1/2" rod and cap #22428

N28° E 22.06' 4" Fir  
N77° E 21.02' 3" Ash  
S59° E 34.55' 3" Fir  
N25° W 49.25' 8" Spruce

Ratified by Peer Group  
in accordance with P.A. 345

Chairman *Norman J. ...*  
Date 12-11-00

Signed by Ronald R. Bischer  
Surveyor's Michigan License No. 22428

Date 11-7-2000