

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
PRESQUE ISLE

(County)

Located In:

Corner Code ~~##~~

1. Public Land Survey	T	<u>36N</u>	R	<u>2E</u>	_____
	T	_____	R	_____	_____
	T	_____	R	_____	_____
	T	_____	R	_____	_____
2. Property Controlling in Section	S	<u>29</u>	T	_____	<u>4</u>
	S	_____	T	_____	_____
3. Miscellaneous Property in Sec.	S	_____	T	_____	_____
	S	_____	T	_____	_____

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
 5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	16	17	18	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, CARL T. KIISKILA, in a field survey on JANUARY 29, 19 97, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

4
 (NO EVIDENCE OF G.L.O. CORNER, B.T.'S, LINE TREES & TOPOGRAPHY, AS CALLED OUT IN THE G.L.O. LINE NOTES; UNLESS NOTED IN ITEM "B" BELOW.)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

4
 FB AND ACCEPTED A 1/2" PIN IN CONC. AS SET BY ORLANDO DOYLE, RLS, FOR THE SE CORNER OF THE PLAT OF SHERWOOD FOREST AND THE SW CORNER OF THE NE1/4 OF THE NW1/4 OF SEC. 29.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

4
 FOUND 4" CONC. MON. SET CARSDNITE POST 1' +/- NORTH.
 UTILITY POLE N47°N 25.16'
 18" RED PINE N50°E 40.94'
 6" N.PINE S60°E 24.25'



Signed by Carl T. Kiiskila Date 2-27-97

Surveyor's Michigan License No. 33981