

State of Michigan Remonumentation Program  
For Presque Isle County

PRESQUE ISLE COUNTY  
RECORDED

LAND CORNER RECORDATION CERTIFICATE 94 SEP -6 AM 10:11  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in  
Presque Isle  
REMONUMENTATION

SURVEY &

APR 25 1995

COMMISSION

Located In:

Corner Code #

- |                                       |   |     |   |    |      |
|---------------------------------------|---|-----|---|----|------|
| 1. Public Land Survey                 | T | 36N | R | 2E | D-11 |
|                                       | T |     | R |    |      |
|                                       | T |     | R |    |      |
|                                       | T |     | R |    |      |
| 2. Property Controlling in Section    | S |     | T | R  |      |
|                                       | S |     | T | R  |      |
| 3. Miscellaneous Property in Sec.     | S |     | T | R  |      |
|                                       | S |     | T | R  |      |
| 4. Lot No. _____, Recorded Plat _____ |   |     |   |    |      |
| 5. Private Claims _____               |   |     |   |    |      |

*Jane M. Lamb*  
REGISTER OF DEEDS

LIBER 311 PAGE 127

Register of Deeds Stamp & File Number

I, Norman J. Quaine in a field survey on April 7, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

|    | A  | B  | C  | D  | E  | F  | G | H | I | J | K | L | M |
|----|----|----|----|----|----|----|---|---|---|---|---|---|---|
| 2  | 6  | 5  | 4  | 3  | 2  | 1  |   |   |   |   |   |   |   |
| 3  |    |    |    |    |    |    |   |   |   |   |   |   |   |
| 4  | 7  | 8  | 9  | 10 | 11 | 12 |   |   |   |   |   |   |   |
| 5  |    |    |    |    |    |    |   |   |   |   |   |   |   |
| 6  | 18 | 17 | 16 | 15 | 14 | 13 |   |   |   |   |   |   |   |
| 7  |    |    |    |    |    |    |   |   |   |   |   |   |   |
| 8  | 19 | 20 | 21 | 22 | 23 | 24 |   |   |   |   |   |   |   |
| 9  |    |    |    |    |    |    |   |   |   |   |   |   |   |
| 10 | 30 | 29 | 28 | 27 | 26 | 25 |   |   |   |   |   |   |   |
| 11 |    |    |    |    |    |    |   |   |   |   |   |   |   |
| 12 | 31 | 32 | 33 | 34 | 35 | 36 |   |   |   |   |   |   |   |
| 13 |    |    |    |    |    |    |   |   |   |   |   |   |   |

A. Description of original monument and accessories and/or subsequent restoration:

|                     |                                     |
|---------------------|-------------------------------------|
| D-11                |                                     |
| GLO Notes           | Spruce 7" S07° E 31 Lks.            |
| Resurvey 1856       | Cedar 9" N25° E 31 Lks.             |
| January 1947        | Concrete Monument                   |
| Doyle Eng. Records  | N30° W 48.8' 7" Balsam              |
| From miscellaneous  | N12° E 23.11' 6" Spruce             |
| Records at Porter's | N30° E 20.46' 9" Cedar Stump (Govt) |
| Survey              | N57° E 47.4' 7" Cedar               |

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

|                              |                                     |
|------------------------------|-------------------------------------|
| D-11                         |                                     |
| 4-7-94                       | Fd. Conc. Mon.                      |
| Presque Isle County          | N30° E 20.46' 9" Cedar Stump O.B.T. |
| State Remonumentation        |                                     |
| Norman J. Quaine             |                                     |
| #33984, Porter's Survey P.C. |                                     |

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

|                          |  |
|--------------------------|--|
| D-11                     |  |
| Conc. Mon.               |  |
| S02° E 55.62' 12" Balsam |  |
| N73° E 24.00' 7" Cedar   |  |
| N40° E 15.34' 8" Cedar   |  |
| S49° W 76.34' 9" Aspen   |  |

Ratified by Peer Group  
in accordance with F.A. 345  
Chairman *Delmer E. Porter*  
Date July 27, 1994

Signed by *Norman J. Quaine*  
Surveyor's Michigan License No. 33984

Date Aug 17, 1994

2396