

1995 STATE OF MICHIGAN REMONUMENTATION

JAN 17 1996

PRESQUE ISLE COUNTY RECORDED

2449

COMMISSION LAND CORNER RECORDATION CERTIFICATE

95 DEC 14 AM 10:29

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Presque Isle Located In: (County)

Corner Code #

Table with 4 columns: Item, Survey Type, Section, Corner Code. Includes Public Land Survey, Property Controlling in Section, and Miscellaneous Property in Sec.

James M. Lamb REGISTER OF DEEDS

LIBER 316 PAGE 936

Register of Deeds Stamp & File Number

4. Lot No. Recorded Plat
5. Private Claims

Grid table with columns A-M and rows 2-13. Contains numerical data for recording purposes.

I, James A. Beck in a field survey on May 17, 1995 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Table with 3 columns: Corner Code, Date/Event, Description. Includes 1856 Government Resurvey, Sept. 22, 1976 Found 4" pipe, and Nov. 29, 1978 Corner recorded by Delmer E. Porter.


B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E6 May 17, 1995: Remonumentation by James A. Beck, P.S. 21559. Found conc. monument and brass cap and one witness from prior recordation by Delmer E. Porter, P.S. 15410 at extension of two-track road running South, at Northerly side of two-track running West, and 27' Westerly of gravel highway running Northwest and Southeast. old witness found: S05°W 51.45 17" N. Pine (set cap P.S. 21559)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Filed by Peer Group in accordance with E.A. 345 James A. Beck & Delmer E. Porter State 11/18/95

Concrete monument and brass cap old: S05°W 51.45 17" N. Pine (set cap P.S. 21559) N61°W 40.42 9" Oak (set cap P.S. 21559) S48°W 29.31 4" W. Pine (set cap P.S. 21559) S25°E 57.60 10" N. Pine (set cap P.S. 21559)



Signed by James A. Beck Surveyor's Michigan License No. 21559

Date 11-18-1995