LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF–:	LOCATED IN–:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 22 N., R. 3 W.	K- 12
2. PROPERTY CONTROLLING IN SECTION 36	,T. 22 N., R. 3 W.	3; 10; 14
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram – over) were, in a field survey on October 2, 1974, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19__ , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

K-12 Set by proportionate measurement between section corners.

3 Set by standard survey procedure.

10 Set by standard survey procedure.

14 Found corner as established in previous survey by Marcus Schaaf.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-12			3			10		
Set DNR monument			½"x24" iron bar			Set ½"x30"iron bar		
8" J. Pine	N55½°E	26.5	6" J. Pine	N71°E	45.5	6" B. Oak	N27°W	20.2
5" R. Pine	West	20.8	8" B. Oak	N47°W	33.7	5" B. Oak	S86°E	320

14
Left 1¼" pipe in place
7" J. Pine N48°E 26.9
Face of power pole
N20°W 100.3

SIGNED BY Kenneth J. Ostling DATE 12

STATE OF MICHIGAN KENNETH J. OSTLING L. SURVEYOR 10068 (SEAL) REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ (CHIEF OF SURVEY PARTY) DATE _____

APPROVED AND SIGNED BY _____ (MICHIGAN REGISTERED LAND SURVEYOR) DATE _____ (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ ROSCOMMON COUNTY

Form No. MLM735
DOUBLEDAY BROS. & CO., KALAMAZOO, MICH.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS