SUNVEY & SEMONUMENTATION

5758

MAY 2.8 1997

COMMISSION CORNER RECORDATION CERTIFICATE

	Filing Require	ement of Act /4, Mich. P.A. 19	370
For corners in			
Roscommon	Located in:	Corner Code ##	
(County)			CTITE OF WEIGHT
1 Public Land Survey	T 22NR 3W	G-6	STATE OF KICHIGAN
1. Public Land Survey	TR		ROSCOMMON COUNTY
	T R	1	RECORDED
	T R		15 AUG 96 10:47 A.M.
2. Property Controlling	S T R	Deg #3	10 000 \0 10-41 W:11
in Section	\$ T R		ROBERT W. SKITH
3. Miscellaneous	\$ T R		Register of Deiss នៃជាទី & គឺរ៉ាំខំ Number
Property in Sec.	S T R		
			A B C D E F G H I J K L
5. Private Claims			— , , , , , , , , , , , , , , , , , , ,
			3
, J. Dean Geers	in a field supply as Wife	bber . 19 95 .	5
		of 1970, the corner points mentioned	
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the			13-13-14-1-13-
current manual of survey instru	uctions of the United States Depar	rtment of the Interior, Bureau of Land	7 + + + + + + + + + + + + + + + + + + +
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a			
Court of Law; established, re-established, monumented, re-monumented, recovered, found as			* - - - - - - - - - - - - - - - - - - -
expressed below:			10 30 -29 -28 -27 -26 -25
NOTE: Not more than 4 ca	orners, all in the same town a	ind range, may be recorded	¹¹
on this certificate.	•	· •	12 31 32 33 34 35 36
			13
A. Description of original	monument and accessories an	nd/or subsequent restoration:	,

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

See Remonumentation Dossier for this corner and LCRC recorded in Liber 3, Page 201

Found Roscommon County std. mon. in mon. box ± 1.5 feet North of centerline of M-55 as recorded in Liber 3, Page 23.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Std. Roscommon County mon. in mon. box

S 59° E - 102.52 - Found Nail in Westerly Leg Post of Sign S 05° W - 51.55 - Face of Steel Fence Post N 05° W - 90.62 - Southeast Corner of Building

N29°E - 67.87 - 4" Oak

PEER GROUP APPROVAL
DATE 8-8-1996

Marvin E. Myers, P.S.
County Surveyor

Signed human	Date 7-22-96
Survey of Michigan Lenge No. 23977	FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 197
GEERS	PEATED TWY OSSEAL

1, arei 3 Pala 318