

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich P.A. 1970

28 APR 99 11:51 A.M.

For corners in
Roscommon County

ROBERT W. SMITH
REGISTER OF DEEDS

	Located in:	Corner Code #
1. Public Land Survey	T22N R3W	G-8
	T	R
	T	R
	T	R

I, Larry L. Cavanagh, in a field survey April, 1999, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in line 1 above was in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

FILE IN LIBER 3 OF LAND CORNERS
Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

WILLIAM BURT 1849
SET POST
Y PINE 16 N36°E 21
W PINE 9 S75°W 15

GOSLING CZUBAK ASSOC., RLS 1992
FD "T" IRON
S24°W 37.53' OAK 24'/FD NAIL
N74°E 26.62' PINE 14'/FD NAIL
N12°W 17.42' B FIR 14'/SPK
N55°W 35.09' OAK 6'/SPK
EAST 0.1' OAK 16'/FACE

FRANCIS E. SPICER, RLS 1973
SET "T" IRON
18' OAK S20°W 37.53'
18' OAK N70°W 25.94'
14' PINE N70°E 26.62'
14' POPLAR S20°E 33.78'

LARRY L. CAVANAGH, PS 1993
L790, P553
FD "T" IRON
SAME WITNESSES AS ABOVE

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND "T" IRON (DRIVEN IN BASE OF OAK)
24' OAK (DEAD) S24°W 37.53'
14' PINE (DEAD) N74°E 26.62'
16' OAK EAST 0.10'
14' B FIR N12°W 17.42'

THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 1/2" X 18" CAPPED STEEL ROD OVER TOP OF T-IRON (17614)
WT: NAIL & TAG IN 14' B FIR N12°W 17.42(OLD)
NAIL & TAG IN 6' OAK N50°W 35.05'
NAIL & TAG IN 16' W OAK S50°W 8.56'
NAIL & TAG IN 16' OAK S50°E 0.45'
CARSONITE POST N50°W 1.4'

**ROSCOMMON COUNTY
PEER GROUP APPROVAL
DATE APRIL 19, 1999**

Marvin E. Myers
**Marvin E. Myers, P.S.
County Surveyor**



Signed by *Larry L. Cavanagh* Date April 23, 1999
Surveyor's Michigan License NO. 17614

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983