

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. 24 N. 9., R. 1 <input checked="" type="checkbox"/> W.	I-10; J-11; K-11;
2. PROPERTY CONTROLLING IN SECTION _____	26, T. 24 N. 9., R. 1 <input checked="" type="checkbox"/> W.	16
3. MISCELLANEOUS PROPERTY IN SECTION _____	, T. _____ N. S., R. _____ E. W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl R. Johnson, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on April 15, 1985, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. Continued:

<u>16</u>	<u>K-11</u>
Set 5/8" Bar w/cap at fd 1/2" bar	Set DNR mon at fd 1" pipe
12" Red Pine N35°E 63.1'	8" Red Pine N32°W 34.4'
5" Jack Pine N45°W 35.8'	9" Red Pine N56 1/2°E 46.7'
4" Cedar Post w/loc tag N4°E 10.0'	

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- I-10 - Found 1/2" bar w/cap set by Henning and used in previous survey in NW 1/4 of section.
- J-11 - Set corner at found 1/2" bar by Henning, midway and on line between section corners.
- 16 - Set corner at found 1/2" bar by Henning, midway and on line between section corners to east and 1/4 corner to west.
- K-11 - Set corner at found 1" pipe in intersection of roads.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<u>I-10</u>	<u>J-11</u>
Found 1/2" bar w/cap (Henning)	Set DNR mon. at fd 1/2" bar
12" Red Oak S70°E 67.7'	8" Red Pine N17°W 19.7'
14" (Twin) White Oak N57°E 99.1'	8" Red Pine S33°W 50.3'
5" Cedar Post w/loc tag S86°E 55.0'	6" Cedar Post w/loc tag N4°E 5.0'

SIGNED BY *Carl R. Johnson*  
 SURVEYOR'S MICHIGAN REGISTRATION NO. 30083

DATE 4/3/85



FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CHIEF OF SURVEY PARTY  
 APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_ ROSCOMMON COUNTY

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET