

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

| FOR CORNERS OF --: | LOCATED IN --: | CORNER CODE NUMBER |
|---|------------------------------|--------------------|
| 1. PUBLIC LAND SURVEY _____ | T. 24 N. R. 2 W. ● | D-13; |
| 2. PROPERTY CONTROLLING IN SECTION 32 _____ | T. 24 N. R. 2 W. ● | 13-16; 13 |
| 3. MISCELLANEOUS PROPERTY IN SECTION _____ | T. _____ N. R. _____ E. W. ● | |
| 4. LOT NO. _____, RECORDED PLAT _____ | | |
| 5. PRIVATE CLAIMS _____ | | |

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, KENNETH J. OSTLING, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on DECEMBER 12, 1983, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 13-16 - SET CORNER BY STANDARD SURVEY PROCEDURE FOR THE SUBDIVISION OF SECTIONS.
- 13 - SET CORNER BY STANDARD SURVEY PROCEDURE FOR THE SUBDIVISION OF SECTIONS.
- D-13 - SET CORNER FROM NBTS BY G.F. DELAMATER IN 1929 SURVEY.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

| <u>13-16</u> | <u>13</u> | <u>D-13</u> |
|-------------------------|-------------------------|-----------------------------|
| SET 5/8" ROD W/RLS CAP | SET 5/8" ROD W/RLS CAP | SET DNR MONUMENT |
| 16" J. PINE N15°W 16.9' | 14" R. PINE N20°E 10.3' | 10" HEMLOCK N34°W 50.7' |
| 5" R. OAK S18°E 21.9' | 10" R. PINE S43°E 29.0' | 16" CEDAR N69°W 26.5' |
| SET 5" CEDAR POST W/LOC | SET 4" CEDAR POST W/LOC | 6" CEDAR S37°W 21.5' |
| TAG BY CORNER | TAG BY CORNER | SET 4" CEDAR POST BY CORNER |

(NW Cor of S 1/2 of SE 1/4 ~ SE 1/4)



SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ ROSCOMMON COUNTY