LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. 24 N., R. 2 W.	E-13;
2. PROPERTY CONTROLLING IN SECTION 32	T. 24 N., R. 2 W.	16; E-13, 14
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. S., R. _____ E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, KENNETH J. OSTLING, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on DECEMBER 12, 19 83, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. CONTINUED:

E-13, 14

SET 5/8" ROD W/RLS CAP
14" R. OAK S37°E 49.3'
12" R. OAK S30°W 77.9'
4" CEDAR POST S39°E 5.0'
(NE Cor of S 1/2 of SE 1/4 ~ SE 1/4)

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

16 - SET CORNER BY STANDARD SURVEY PROCEDURE FOR THE SUBDIVISION OF SECTIONS.
E-13 - FOUND 1 1/4" PIPE IN PLACE, AS LOCATED IN 1929 SURVEY BY G.F. DELAMATER, AND USED IN SUBSEQUENT SURVEY BY G.D. HENNING. OBT STUMPS IN PLACE.
E-13,14 - SET CORNER BY STANDARD SURVEY PROCEDURE FOR THE SUBDIVISION OF SECTIONS.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

16
SET 5/8" ROD W/RLS CAP
8" R. PINE S89°W 32.8'
3" R. PINE N37°E 39.0'
SET 5" CEDAR POST W/LOC TAG BY CORNER

E-13
LEFT 1 1/4" PIPE IN CONCRETE
9" R. OAK N10°E 24.7'
12" R. OAK S56°E 49.5'
SET 5" CEDAR POST W/LOCATION TAG BY CORNER

STATE OF MICHIGAN
KENNETH J. OSTLING
LAND SURVEYOR
No. 10068
REGISTERED LAND SURVEYOR

SIGNED BY Kenneth J Ostling DATE 2/6/8

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

ROSCOMMON COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET