

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY.....	T. 24 N. R. 4 W. ●	H-2
2. PROPERTY CONTROLLING IN SECTION.....	T. 24 N. R. 4 W. ●	3; 4; 8; 12
3. MISCELLANEOUS PROPERTY IN SECTION.....	T. S. R. E. W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER _____

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on December 19, 1979, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

~~--- Description of original monument and accessories and/or subsequent restoration ---~~

C. (continued)

	8				12
Set 5/8" Rerod w/RLS Cap & cedar post					Set 5/8" Rerod w/RLS Cap & cedar post
4" R. Pine S10°W	25.3				20" W. Pine S30°E 13.9
4" Balsam S84°W	25.1				3" W. Pine N66°W 16.4

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 2 Set corner by standard survey procedure for the subdivision of sections.
- 3 Set by standard survey procedure for the subdivision of sections.
- 4 Set by standard survey procedure for the subdivision of sections.
- 8 Set by standard survey procedure for the subdivision of sections.
- 12 Set by standard survey procedure for the subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

	11-2		3		4
Set 5/8" Rerod w/RLS Cap & cedar post			Set 5/8" Rerod w/RLS Cap & cedar post		Set 5/8" Rerod w/RLS Cap & cedar post
14" R. Pine S31°E	34.4		4" Balsam S59°W	24.4	6" Maple S28°E 6.4
6" Maple S31°W	3.5		5" Maple S27°E	11.3	18" W. Pine N74°E 36.0

SIGNED BY Kenneth Ostling DATE 1/15/80

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY _____ DATE _____

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ ROSCOMMON COUNTY