

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T 24 N. R. 4 W.	G-2; H-1; H-3
2. PROPERTY CONTROLLING IN SECTION	T. N. R. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. R. W.	
4. LOT NO.---, RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on August 16, 1971, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on August 16, 1971, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and of subsequent restoration

B. Description of corner evidence found and of method applied in restoring or re-establishing corners

- 2 Found 2" pipe in concrete base as established by M. Schaaf survey in 1940's.
- 1 Found 2½" pipe, probably as established in previous survey by M. Schaaf, R.L.S., and used by M.D.S.H. and other surveys.
- 3 Restored corner from witnesses of record. Previously established by A. E. Newman 1903, from U.S.B.T. while making plats of M. C. Park. Found base of M. Schaaf monument in place when setting monument.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner

G-2	H-1	H-3
Set DNR Monument	Left 2½" pipe in place	Set DNR Monument & Cedar Post
18" R. Pine S10°E 26.82	8" Cedar S10°W 21.9	9" Oak S45°W 16.9
6" R. Pine N78°E 12.14	10" Spruce N38°W 17.9	18" Oak N16°W 32.41

SIGNED BY Kenneth J. Ostling

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:


SIGNED BY _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____
MICHIGAN REGISTERED LAND SURVEYOR

DATE 10/12/71

DATE _____

DATE _____



(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO.

ROSCOMMON COUNTY