LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY	₁ 24	₩ H-4; H-5	
2. PROPERTY CONTROLL: 10 ING IN SECTION	.1 24	♥ 3; 4	
3. MISCELLANEOUS PROPERTY IN SECTION-	.1	i .	
4, LOT NO RECO	ORDED PLAT		
5. PRIVATE CLAIMS		REGISTRA OF DEEDS FILING NUM	
re-established, monumented, re-i and rules therefore as required in Bureau of Land Management or and 5 above were, in a field surve as expressed below and in contor Decree of a Court of law:	nes I and 2 above were, nonnimented, recovered in the current manual of by a decree of a court of you	rehy certify that under requirements of PA 74. Michigan I is, in a field survey on September 27. , 19,79. , I or restored as expressed below and in conformance with I survey instructions of the United States Department of its law. Furthermore, that the corner points mentioned in 19. , found recovered, restored, established or roof the Michigan State Board of Registration for Land Survey.	, established h regulation the Interior n Imes 3, 4 re-established
 Немпрыны об обдінавляння C. (continued) 	म्प्राप्ति न्यास्य न्यान्यक्रमान्यम् स्थाप		
c. (00.01.1.aca)	PK in 120 R	4 con Bar w/RLS Cap R. Pine N55 ⁰ W 16,29 R. Pine N36 ⁰ E 35,49	

- B. Description of corner evidence found and or method applied in restoring or to establishing corner.
- Set by standard survey procedures (at intersection of true 4 lines) for the subdivision of sections.
- Found $\frac{1}{2}$ ⁿ iron bar as previously established by G. F. DeLaMater in survey of Sec. 15. Also used in M.D.S.H. survey.
- Found 12" pipe at corner as established in a previous survey.
- Set by standard survey procedure for the subdivision of sections.
 - C. Description of monument for corner and accessories established to perpetuate locating the position of the corner

11-4			H-5			3			
Set	Set 5/8" iron bar w/cap			Set DNR Monument			Set 5/8" Iron Bar w/RLS Cap		
. 411	R. Oak	N70°W	40.30	4" W. Pine	S40°E	48.62	4" W. Pine	S35 ^O W	24.41
12"	W. Oak	S30°W	15.95	10" W. Pine	S62°W	36.25	12" Maple	S52 ^O E	18.52
				Cedar Post	North	201	-		

SIGNED BY General hy Colling

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES.

SIGNED BY

DATE

DAIII

APPROVED AND SIGNED BY: MICHIGAN REGISTERED LAND SURVEYOR

ISEALI

SURVEYOR'S MICHIGAN REGISTRATION NO.

ROSCOMMON COUNTY