

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	E. 24 N. R. 4	G-3; G-4; G-5
2. PROPERTY CONTROLLING IN SECTION 10	T. 24 N. R. 4	8
3. MISCELLANEOUS PROPERTY IN SECTION	N. R.	
4. LOT NO. RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan, P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on September 26, 1979, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 19, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 3 Found 2" pipe at corner as established in previous survey by M. Schaaf.
- 4 Found axle shaft at corner as established in a previous survey by an unknown surveyor.
- 5 Found 1" iron bar at corner as established by an unknown surveyor.
- 8 Set by standard survey procedure for the subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-3	G-4	G-5
Set DNR Monument	Set DNR Monument	Set DNR Monument
6" Maple in Clump of 6	6" Spruce N81°W 83.40	12" R. Pine S25°E 29.72
S67°W 39.28	8	10" J. Pine N15°W 10.62
8" R. Pine N42°W 67.62	Set 5/8" Iron Bar w/RIS Cap	
	10" W. Oak N47°E 45.5	
	10" W. Oak N42°W 37.6	

SIGNED BY Kenneth J. Ostling
SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

DATE 1/5



FOR STATE AND UNITED STATES AGENCIES.

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ ROSCOMMON COUNTY