

RECORDED/FILED

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

1997 SEP 26 P 3: 26

For corners in SAGINAW COUNTY REMONUMENTATION

MILDRED H. DODAK  
REGISTER OF DEEDS  
SAGINAW COUNTY, MI.

LIBER 2027 PAGE 449

*Lib 7 Page 140*  
Register of Deeds Stamp & File Number

<u>SAGINAW</u> (County)	Located in: B'RUN TWP.	Corner Code #
1. Public Land Survey	T <u>10N</u> R <u>6E</u>	<u>M-11</u>
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
 5. Private Claims \_\_\_\_\_

I, BRIAN D FERGUSON, in a field survey on JUNE 17, 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	16		17		18		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

A. Description of original monument and accessories and/or subsequent restoration:

M-11: WOOD POST SET BY WAMPLER IN 1822

APPROVED BY PEER GROUP  
P.A. 345 OF 1990  
SAGINAW COUNTY  
*9-18-97 BDF*

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

M-11: FOUND 1/2" RE-BAR  
LCRC RECORDED IN L 1 PG 4  
SURVEYS RECORDED IN L 1573 PG 2026, 1335 PG 468

ACCEPTED BY THE PEER REVIEW GROUP AS THE BEST  
AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER


C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-11: SET 5/8" ROD W/3" BRASS CAP IN MONUMENT BOX  
N20W 42.55' TOP CTR MBT RISER  
S45E 74.44' TOP CTR MBT RISER  
S45W 43.44' STREET SIGN POST  
S85E 16.95' N. LEG OF STREET SIGN

SURVEY &  
REMONUMENTATION

MAR 18 1998

SECTION



Signed by *Brian D. Ferguson*  
Surveyor's Michigan License No. 26454

Date SEPTEMBER 25, 1997