

APPROVED BY PEER GROUP
P.A. 345 OF 1990
SAGINAW COUNTY

2-1 [Signature]

SAGINAW COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED/FILED

For corners in

KOCHVILLE TOWNSHIP

<u>SAGINAW</u> (County)	Located in:	Corner Code #
1. Public Land Survey	T <u>13</u> N R <u>4</u> E	<u>F-11</u>
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

1999 SEP 29 A 8 05

MILDRED M. DODAK
REGISTER OF DEEDS
SAGINAW COUNTY, MI.
LIBER 2144 PAGE 760

Lib 8 Page 25

Register of Deeds Stamp & File Number

- 4. Lot No. _____, Recorded Plat _____
- 5. Private Claims _____

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, Brian D Ferguson, in a field survey on JUNE 28, 19 99 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

WOOD POST SET BY J. WAMPLER IN 1822, NO EVIDENCE OF ORIGINAL CORNER REMAINS
LCRC BY JOHN MARTIN IN 1973, L 2, PG 100
LCRC BY EUGENE GOSS IN 1973, L 2, PG 147

RECORDED
MAR 09 2000

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1" PIPE AT LOCATION OF LCRC L 2 PG 100

SECTION

ACCEPTED BY PEER GROUP AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 5/8" REBAR W/ 3" BRASS CAP IN MONUMENT BOX
N50E 47.47' NAIL IN NW FCE UTIL POLE
S35E 33.19' TOP CTR BOLT OF HYDRANT
SOUTH 54.00' NAIL IN N FCE PWR POLE
N65W 107.93' NAIL IN S FCE UTIL POLE



Signed by Brian D Ferguson
Surveyor's Michigan License No. 26454

Date SEPTEMBER 23 1999