

LAND CORNER RECORDATION CERTIFICATE

NOV 19 1993

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

COMMISSION

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. <u>11</u> N. S., R. <u>12</u> E. W.		<u>G-13, H-13</u>
2. PROPERTY CONTROLLING IN SECTION _____, T. _____ N. S., R. _____ E. W.		
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____ N. S., R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

RECEIVED FOR RECORD
 93 NOV -8 PM 1:39
 LIBER NO. 1 PAGE NO. 388
 ESTHER LEE
 REGISTER OF DEEDS
 SANILAC CO., MICHIGAN
 REGISTER OF DEEDS STAMP AND FILING NUMBER

I, John A Milletics, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on Aug 21, 1993, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

G - 13 Found P.K. nail as recorded in a plat recorded in Liber 3 Slide 266 Sanilac County Records.

H - 13 Found R/R Spike as recorded in Liber 4 Page 164 of the Sanilac County Records.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

G - 13
 SW Cor Section 34 T11N-R12E
 Found P.K. nail

H - 13
 S 1/4 Cor Section 34 T11N-R12E
 Found R/R Spike

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G - 13	H - 13
SW Cor Section 34 T11N-R12E	S 1/4 Cor Section 34 T11N-R12E
Set Monu Box	Set Monu Box
S45°E 46.35' to a nail in a Tele Pole	N45°W 35.35' to a nail in 15" Maple
S10°W 43.75' to a nail in a 24" Oak	N05°E 29.20' to a nail in 30" Maple
N45°W 40.45' to a Stop Sign Post	N75°E 89.30' to a nail in 36" Maple

SIGNED BY John A Milletics DATE Nov 4, 1993
 SURVEYOR'S MICHIGAN REGISTRATION NO. 25859

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY
 APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

