

REMONUMENTATION CORNER

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Sanilac (County)

Located In:

Corner Code #

LIBER 1 PAGE 393
RECEIVED FOR RECORD

93 DEC 14 PM 3:00

LIBER NO. 1 PAGE NO. 393
ESTHER LEE
REGISTER OF DEEDS
SANILAC CO., MICHIGAN

Register of Deeds Stamp & File Number

- 1. Public Land Survey T 11N R 13E B - 13, C - 113
2. Property Controlling in Section S T R
3. Miscellaneous Property in Sec. S T R
4. Lot No. , Recorded Plat
5. Private Claims

I, John A Milletics, in a field survey on Aug 23, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Grid table with columns A-M and rows 2-13. Contains numbers 1-36 in a grid pattern.

A. Description of original monument and accessories and/or subsequent restoration:

- B - 13 Found P.K. nail in blacktop equal distance from SW Cor and SE Cor of Section
C - 13 Found P.K. nail in blacktop used survey Recorded by Bert Walker Sept. 1993 to verify location.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- B - 13 S 1/4 Cor Section 31 T11N-R13E Found P.K. nail
C - 13 SE Cor Section 31 T11N-R13E Found P.K. nail

SURVEY &
REMONUMENTATION
1993
COMMISSION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- B - 13 S 1/4 Cor Section 31 T11N-R13E Set Monu Box East 3.53' to the N 1/4 Cor Sec. 5 (Monu Box) S10°E 43.90' to a nail in a 30" Spruce N45°E 65.55' to a nail in a Power Pole N45°W 61.40' to a nail in a Tele Pole
C - 13 SE Cor Section 31 T11N-R13E Set Monu Box West 4.33' to the NW Cor Section 4 (Monu Box) N10°W 66.65' to a nail in a Power Pole N10°E 65.05' to a nail in a Power Pole S45°E 26.90' to the SW cor of a Headwall

Signed by John A Milletics Date Dec 13, 1993
Surveyor's Michigan License No. 25859