

# ST. CLAIR COUNTY, MICHIGAN OFFICIAL GOVERNMENT CORNER



## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

RECEIVED  
 DEC 29 AM 9:02  
 REGISTERED DEEDS  
 ST. CLAIR COUNTY

Register of Deeds Stamp & File Number

	Located In: Wales Twp.	Corner Code # M-7
1. Public Land Survey	T <u>6N</u> R <u>15E.</u>	<u>M-7</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	<u>Sec. 1</u>
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
 5. Private Claims \_\_\_\_\_

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, John R. Lansky in a field survey on Sept. 20-24, 1993  
 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 1 corner, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

1. Post-- Original Gov't Survey
2. Ford Axle-Per Old Surveyor's Rec. S.C.Co.
3. Iron Rod Per Certificates L. 2 P.170, L.4 P.366

STATE PLAIN COORDINATES

N. \_\_\_\_\_

E. \_\_\_\_\_

ELEVATION \_\_\_\_\_

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 5/8" Iron Rod

2159A000 12/29/93HSSU# 9.00  
 \*\*000J\*\*

2159A000 12/29/93SRE# 2.00  
 \*\*000I\*\*

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

5/8" Iron Rod (Same point as previously rec. L.2 P.170, L.4 P.366)

S.W. 46.05 ft. Set PK nail & Tag in D.E. Pole  
 W.S.W. 104.80 ft. " " " "  
 N.W. 44.28 ft. " " " in Guy Pole  
 S'yly 31.14 ft. to Sec. Corner for Kimball Twp.  
 See attached sketch for additional indormation.



Signed by John R. Lansky  
 Surveyor's Michigan License No. 18659

Date Sept. 29, 1993

PA 345-1990  
 PEER COMMITTEE

APPROVED AS AN OFFICIAL GOVERNMENT CORNER BY ST. CLAIR COUNTY:

APPROVED 11-16-93

Signed By: \_\_\_\_\_  
 St. Clair County Land Surveyor

Date \_\_\_\_\_

Surveyor's Michigan License No. \_\_\_\_\_