

ST. CLAIR COUNTY, MICHIGAN OFFICIAL GOVERNMENT CORNER



LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

	Located In: Wales Twp.	Corner Code #:
1. Public Land Survey	T <u>6N</u> R <u>15E.</u>	<u>M-8</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	<u>Seg. 1</u>
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

REGISTERED
 ST. CLAIR COUNTY
 REGISTER OF DEEDS
 1993 DEC 29 AM 10:01
 RECEIVED
 Register of Deeds Stamp & File Number

I, John R. Lansky, in a field survey on Sept. 20-24, 1993 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	16	17	18	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

NOTE: Not more than 1 corner, may be recorded on this certificate.

- A. Description of original monument and accessories and/or subsequent restoration:
1. Post-- Per Original Gov't Survey
 2. Nothing Listed on Old Surveyor's Record St. Clair County for this corner.
 3. 1" Iron Bar Per Certificate L.2 P.170
- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
Found Frost Pin (Aprx 1 1/2" Dia)

STATE PLAIN COORDINATES

N. _____


E. _____

ELEVATION _____

2159A000 12/29/93MSSU4 9.00
 0001
 2159A000 12/29/93SSRE4 2.00
 0001

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
Iron Pin (Aprx. 1 1/2" Dia) (Apparently same pt as on Cert. L.2 P.170)

N.E. 37.47 ft. Set PK Nail & Tag in 15" Elm
 W.N.W. 29.45 ft. " " " in 36" Maple
 S.E. 51.96 ft. " " " in Guy Pole
 S'yly 43.00 ft. to West 1/4 Cor. Sec. 19, T.6N., R.16E.
 See attached sketch for additional information.



Signed by John R. Lansky Date Sept. 29, 1993

Surveyor's Michigan License No: 18659

PA 345-1990
 PEER COMMITTEE

APPROVED 11-16-93

APPROVED AS AN OFFICIAL GOVERNMENT CORNER BY ST. CLAIR COUNTY:

Signed By: _____ Date _____
 St. Clair County Land Surveyor

Surveyor's Michigan License No. _____