

**ST. CLAIR COUNTY, MICHIGAN
OFFICIAL GOVERNMENT CORNER**



**LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970**

Located In: _____ Corner Code ~~#~~ _____

- | | | | |
|------------------------------------|---|-------------------|---------------|
| 1. Public Land Survey | | Wales Twp. | |
| | T | 6N. | R 15E. |
| | T | _____ | _____ |
| | T | _____ | _____ |
| | T | _____ | _____ |
| 2. Property Controlling in Section | S | _____ | _____ |
| | S | _____ | _____ |
| 3. Miscellaneous Property in Sec. | S | _____ | _____ |
| | S | _____ | _____ |
- A-1
Seg. #2

REGISTERED
 1995 APR -4 AM 10:27
 REGISTERED
 Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2							
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

Daniel E. Johnson April 17 1995

I, _____, in a field survey on _____, 19____,

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 1 corner, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

LIBER 007 PAGE 187

STATE PLAIN COORDINATES

N. _____

E. _____

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

LIBER 007 PAGE 187



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

"ACCEPTED MICHIGAN DEPARTMENT OF TRANSPORTATION BRASS DISC"
5/8" ROD WITH 1-1/2" BRASS DISC
 E. 34.20 ft. to set PK and County Tag in N face of fence post.
 SE 91.65 ft. " " " " " " " NW face of D.E.P.
 SSW 174.33 ft. to set PK and County Tag in NE face of root of 40" Oak
 NNE 96.45 ft to set PK and County Tag in W face of D.E.P.

Signed by *Daniel E. Johnson*
 Daniel E. Johnson
 13754

Date April 17, 1995

Surveyor's Michigan License No. _____

PA 345-1990
 PEER COMMITTEE
 APPROVED 12-14-93

APPROVED AS AN OFFICIAL GOVERNMENT CORNER BY ST. CLAIR COUNTY:

Signed By: *Daniel E. Johnson*
 St. Clair County Land Surveyor **Daniel E. Johnson**
 13754

Date 7-31-95

Surveyor's Michigan License No. _____

LIBER 008 PAGE 211