

**ST. CLAIR COUNTY, MICHIGAN
OFFICIAL GOVERNMENT CORNER**



**LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970**

	Located In:	Corner Code #
	Kimball Twp.	
1. Public Land Survey	T <u>6N</u> R <u>16E.</u>	<u>A-8</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	<u>Sec 1</u>
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

REGISTERED
 ST. CLAIR COUNTY
 1993 DEC 29 9:02
 RECEIVED
 REGISTER OF DEEDS STAMP & FILE NUMBER

I, John R. Lansky, in a field survey on Sept. 20-24, 1993

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	5	6	7	8	9	10	11	12	13	14	15	16	17
3													
4	7	8	9	10	11	12	13	14	15	16	17	18	19
5													
6	18	17	16	15	14	13	12	11	10	9	8	7	6
7													
8	19	20	21	22	23	24	25	26	27	28	29	30	31
9													
10	30	29	28	27	26	25	24	23	22	21	20	19	18
11													
12	31	32	33	34	35	36	37	38	39	40	41	42	43
13													

NOTE: Not more than 1 corner, may be recorded on this certificate.

- A. Description of original monument and accessories and/or subsequent restoration:
1. This Corner not set in Original Gov't Survey.
 2. Nothing listed on Old Surveyor's Record St. Clair County for this corner.
 3. Iron Rod-- Per Certificate L.6 P.349

STATE PLAIN COORDINATES
 N. _____
 E. _____
 ELEVATION _____

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
Found Iron Rod



- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Iron Rod

N.W. 55.87 ft. Set PK Nail & Tag in 36" Maple
 Easterly 28.45 ft. " " " in P. Pole
 N.E. 73.90 ft. " " " in 15" Elm.
 Northerly 43.00 ft. to East 1/4 Corner of Sec. 24 T.6N., R.15E.,

2159A000 12/29/93MSSU4 9.00
 000J

See attached sketch for additional information.

2159A000 12/29/93SSRE4 2.00
 000J

Signed by John R. Lansky
 Surveyor's Michigan License No. 18659

Date Sept. 29, 1993

PA 345-1990
 PEER COMMITTEE

APPROVED 11-16-93

APPROVED AS AN OFFICIAL GOVERNMENT CORNER BY ST. CLAIR COUNTY:

Signed By: _____
 St. Clair County Land Surveyor

Surveyor's Michigan License No. _____