

FILED

JUN 27 12 46 PM '94

004 PG 032

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Cynthia R. Janett
REGISTER OF DEEDS
ST. JOSEPH COUNTY

For corners in

ST. JOSEPH

(County)

Located In:

Corner Code #

1. Public Land Survey

T 5S R 11W

A-12

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

**SURVEY &
REMONUMENTATION**

AUG 31 1994

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

COMMISSION

5. Private Claims _____

| | A | B | C | D | E | F | G | H | I | J | K | L | M |
|----|----|---|----|---|----|---|----|---|----|---|----|---|---|
| 2 | 6 | | 5 | | 4 | | 3 | | 2 | | 1 | | |
| 3 | | | | | | | | | | | | | |
| 4 | 7 | | 8 | | 9 | | 10 | | 11 | | 12 | | |
| 5 | | | | | | | | | | | | | |
| 6 | 18 | | 17 | | 16 | | 15 | | 14 | | 13 | | |
| 7 | | | | | | | | | | | | | |
| 8 | 19 | | 20 | | 21 | | 22 | | 23 | | 24 | | |
| 9 | | | | | | | | | | | | | |
| 10 | 30 | | 29 | | 28 | | 27 | | 26 | | 25 | | |
| 11 | | | | | | | | | | | | | |
| 12 | 31 | | 32 | | 33 | | 34 | | 35 | | 36 | | |
| 13 | | | | | | | | | | | | | |

I, DAVID W. MOSTROM, in a field survey on MAY 5, 19 94

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
(A-12) WEST 1/4 COR. SEC. 31, T5S, R11W
NO RECORD OF CORNER BEING SET

RATIFIED BY PEER GROUP
IN ACCORDANCE WITH P.A. 345
ON MAY 9, 1994
Willis CO. REPRESENTATIVE

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(A-12)

FOUND VERY OLD 3/4" X 14" LONG BOLT IN PROJECTION OF FENCE LINE TO SOUTH AND IN CENTER OF OLD ROADWAY TO EAST.
BOLT FALLS 20'± NORTH OF FENCE RUNNING TO WEST.



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(A-12)

SET 5/8" X 24" IRON W/STANDARD CAP OVER BOLT FOUND
CORNER FALLS 17.82' NORTH OF CORNER SET AT EAST 1/4 COR. SEC. 36, T5S, R12W
PK NAIL & WASHER 2' HIGH ON E. SIDE OF 6" CHERRY = NORTH 5.67'
PK NAIL & WASHER 2' HIGH ON S. SIDE OF 4" CHERRY = N73°E 4.75'
PK NAIL & WASHER 2' HIGH ON S. SIDE OF 18" W. OAK = N59°W 28.92'
PK NAIL & WASHER 2' HIGH ON S. SIDE OF 8" R. OAK = N82°W 35.97'

Signed by

Date

JUNE 14, 1994

Surveyor's Michigan License No.

32339

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

REMONUMENTATION