

JAN 24 1996

004 PG 017

FILED

DEC 7 10 47 AM '93

COMMISSION LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Cynthia R. Janoff
REGISTER OF DEEDS
ST. JOSEPH CATHOLIC

For corners in

| | | |
|--|--------------------------|----------------|
| <u>ST. JOSEPH</u> <small>(County)</small> | Located In: | Corner Code #: |
| <u>FLOWERFIELD TWP.</u> | T <u>5S</u> R <u>12W</u> | <u>K-12</u> |
| 1. Public Land Survey | T _____ R _____ | _____ |
| | T _____ R _____ | _____ |
| | T _____ R _____ | _____ |
| 2. Property Controlling in Section | S _____ T _____ R _____ | _____ |
| | S _____ T _____ R _____ | _____ |
| 3. Miscellaneous Property in Sec. | S _____ T _____ R _____ | _____ |
| | S _____ T _____ R _____ | _____ |
| 4. Lot No. _____, Recorded Plat _____ | | |
| 5. Private Claims _____ | | |

Register of Deeds Stamp & File Number

I, WAYNE A. MOSTROM, in a field survey on AUGUST 8, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

| A | B | C | D | E | F | G | H | I | J | K | L | M |
|----|----|----|----|----|----|----|---|---|---|---|---|---|
| 2 | 6 | 5 | 4 | 3 | 2 | 1 | | | | | | |
| 3 | | | | | | | | | | | | |
| 4 | 7 | 8 | 9 | 10 | 11 | 12 | | | | | | |
| 5 | | | | | | | | | | | | |
| 6 | 10 | 17 | 16 | 15 | 14 | 13 | | | | | | |
| 7 | | | | | | | | | | | | |
| 8 | 19 | 20 | 21 | 22 | 23 | 24 | | | | | | |
| 9 | | | | | | | | | | | | |
| 10 | 30 | 29 | 28 | 27 | 26 | 25 | | | | | | |
| 11 | | | | | | | | | | | | |
| 12 | 31 | 32 | 33 | 34 | 35 | 36 | | | | | | |
| 13 | | | | | | | | | | | | |

A. Description of original monument and accessories and/or subsequent restoration:

| | |
|----------------------------|--|
| K-12 | |
| GLO | 1974 SURVEY BY MOSTROM & LCRCIN L.-1, P.--69 |
| 12" W.O.= S571/4°W 37LKS | FD. PIPE IN MON BOX |
| 24' W.O.= N533/4°E 153 LKS | P.P.= NE 45.54' |
| | 20" MAPLE = SE 37.21' |

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-12
FOUND 1" PIPE IN MON BOX OVER STONE
PP = NE45.54'
20" MAPLE = SE37.21'



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-12 (1/4 COR. COMMON TO SEC 35 & 36)
SET 5/8"X24" BAR W/STD. CAP OVER STONE
COR IS IN N-S CL & 1' N OF E-W CL RDWY:
N & W IN S. SIDE P.P.= N50°E 45.40'
CL USGS TABLET= N55°E 44.82'
N & W IN SW SIDE 24" MAPLE= S58°E 56.17'
N & W IN SW SIDE 24" MAPLE= S25°E 96.10'

APPROVED BY
PEER GROUP AS
BEST AVAILABLE
EVIDENCE OF CORNER

Signed by *Wayne A. Mostrom* Date 11/11/93
Surveyor's Michigan License No. 14100