

**LAND CORNER RECORDATION CERTIFICATE**  
**Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in  
Schoolcraft  
 (County)

Located In:

Corner Code  $\neq$

1. Public Land Survey	T	R	
	T	R	
	T	R	
	T	R	
2. Property Controlling in Section	S	33T	44R
	S	33T	44R
3. Miscellaneous Property in Sec.	S	33T	44R
	S	T	R

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
 5. Private Claims \_\_\_\_\_

I, Stephan J. Szyszkoski, in a field survey on January 12, 1994, 19\_\_\_\_, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE:** Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	16	17	18	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

**A. Description of original monument and accessories and/or subsequent restoration:**

- (5-Sec.33) Corner not established in the original survey. Found no subsequent record.
- (6-Sec.33) Northeast 1/16 corner, Section 33. Corner not established in the original survey. Found no subsequent record.
- (9-Sec.33) East 1/16 Corner of Section 33. Corner not established in the original survey. Found no subsequent record.

**B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:**

- (5-Sec.33) Found no evidence of prior monumentation at the corner position. Established the corner midway and on a straight line between the Quarter corner 1321.99' North and Center of Section 1321.99' South. The Center was determined at the intersection of straight lines connecting opposite quarter corners and was not monumented in this survey. At the position for the corner, I placed a 1" I.D. iron pipe capped with a 4" dia. cast aluminum MDNR tablet, appropriately stamped.
- (6-Sec.33) Found no evidence of prior monumentation at the corner position. Established the corner at the intersection of straight lines connecting opposite 1/16 corners, the corner to the east being unmonumented as of this date. At the position for the corner, I placed a 1" I.D.x36" iron pipe capped with a 4" dia. cast aluminum MDNR tablet, appropriately stamped.
- (9-Sec.33) Found no evidence of prior monumentation at the corner position. Established the corner midway and on a straight line between Center of Section 1322.53' West and Quarter corner 1322.52' East. The Center of Section is unmonumented as of this date. The Quarter corner between 33-34 was recently recorded by Neil Hill, LS, Michigan Department of Transportation. At the position for the corner, I placed a 1" I.D.x36" iron pipe capped with a 4" dia. cast aluminum MDNR tablet, appropriately stamped.

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

- |  |  |  |
|--|--|--|
| <p>(5) 1" iron pipe with 4" MDNR cap<br/>         Blazed, scribed, and set measuring nails in the following bearing trees:<br/>         5" Maple S3E 59.7' "N1/16 BT"<br/>         14" Hemlock S10E 60.4' "N1/16 BT"<br/>         4" Maple S21W 55.65' "N1/16 BT"<br/>         5" Cherry N72W 58.8' "N1/16 BT"<br/>         Bearings are magnetic.</p> | <p>(6) Set a 1" pipe with 4" MDNR cap.<br/>         Blazed, scribed, and set measuring nails in the following bearing trees:<br/>         16" Cedar N55W 15.95' "NE1/16 BT"<br/>         18" Cedar N28W 18.2' "NE1/16 BT"<br/>         4" Y. Birch N70W 20.45' "NE1/16 BT"<br/>         10" Cedar N50E 24.8' "NE1/16 BT"<br/>         Placed a 5" squared cedar post adjacent.<br/>         Bearings are magnetic.</p> | <p>(9) Set 1" iron pipe with 4" MDNR cap.<br/>         Blazed, scribed, and set measuring nails in the following bearing trees:<br/>         5" Maple N30W 7.45' "E1/16 BT"<br/>         10" Maple N30E 10.2' "E1/16 BT"<br/>         12" Maple N83E 22.9' "E1/16 BT"<br/>         10" Maple S10E 3.35' "E1/16 BT"<br/>         Bearings are magnetic.</p> |
|--|--|--|

Signed by Stephan J. Szyszkoski Date 5-9-94  
 Surveyor's Michigan License No. 33986

