## 1993 REMONUMENTATION PROGRAM

NO C C	LAND CORN	NER RECORDATION CERTIFIC	CATE		-		
COMMISSION For corners in TUSCOLA (County)		INGTON TOWNSHIP  Corner Code #	1970	TUSCOL	48.839 VE	FLUS NO.	ne contraction
1. Public Land Survey	T 10 N R 8 E	<u>M-6</u>		2000 2000 2000 2000 2000 2000 2000 200		Halling &	
2. Property Controlling Sin Section S 3. Miscellaneous S Property in Sec. S	T R T R T R T R T R T R T R T R R T		Register of	Deeds St	amp & F	ile Numb	
4. Lot No, Recorded P 5. Private Claims	lat		1 A B	C D E	FGI	1   J K	( L M
JONATHAN M. FIELD  do hereby certify that under requirements in lines 1 and 2 above were in conform current manual of survey instructions of Management or by a decree of a Court of above were in conformance with the rule court of Law; established, re-establishers appressed below:  NOTE: Not more than 4 corners, on this certificate.	is of P.A. 74, Michigan P.A. nance with regulations are the United States Depart Law and/or that the corners of the Michigan Board ished, monumented, repart in the same town	A. of 1970, the corner points mentioned nd rules therefore as required in the timent of the Interior, Bureau of Land per points mentioned in lines 3, 4 and 5 of Land Surveyors or by a Decree of a -monumented, recovered, found as and range, may be recorded	2 6 3 4 7 5 6 18 7 8 19 9 10 30 11 12 31 13	20	9 1 21 2 28 2	5   14 2   23	12 13 4 24 25 36
A. Description of original monum- 1821 GLO - WAMPLER, D.S SE 1892 FELTON, C.S SET FROM: 1974 COMMOMWELATH ASSOC SW. S30E 4.90' 18" MAPLE, S2: 1974 SWARTS, P.S.#16945; LCRC	T 1/2 MILE POST; B) MEAS NO OBJECT; MARTS, P.S.#16945; OW 8.49' 48" OAK	EECH 12" S33W 1 LK., PINE 36" STATED, PINE 32" S71W 28 1/2LJ SURVEY L.444, PG.223-225 - SE	N70E 4LKS. KS., PINE 25 T 1/2" IRON;	N40E 19	86' 10"	OAK	
1993 ROWE ENG FIELD, P.S.#	37276; FND 1/2" ROI	applied in restoring or reestablishind 2.5'E & 7'N OF FENCE CORNERS IN THE SAME POSITION AS 1974	(FENCE RUNS				
ACCEPTED FND 1/2" ROD AS	BEST EVIDENCE OF	ORIGINAL CORNER POSITION					



SEE 2	ALSO	BACK	0F	THIS	FORM
-------	------	------	----	------	------

Description of monument for corner and accessories established to perpetuate locating the position of the corner: N-6 SET STANDARD MONUMENT (5/8" ROD W/RRASS CAR TYLEONOMY.

SET STANDARD MONUMENT (5/8" ROD W/BRASS CAP IN CONC)
N39°E, 20.26' SET NAIL W/REMON TAG IN NW FACE 14" W. OAK
S64°E, 4.77' SET NAIL W/REMON TAG IN N. FACE TRIPLE 8" MAPLE
S02°W, 9.91' SET NAIL W/REMON TAG IN E. FACE TRIPLE 14" W. OAK

S65°W, 13.68' SET NAIL W/REMON TAG IN NW FACE 10" W. PINE

N36°W, 28.72' SET NAIL W/REMON TAG IN NE FACE 6" MAPLE

NO5°W, 41.38' SET NAIL W/REMON TAG IN E. FACE TWIN 14" W. OAK



Signed b	y Jan	the.	m:	Field
	//			

Date

Surveyor's Michigan License No. 37276

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1971 REVISED JAN., 1981 ADAPTED FOR WORD PROCESSING MARCH, 1981

**APPROVED** 12-13-1993





SECTION 13 TION-R8E

2640'	2588.52	2812.08**	2579.94
1821 GLO	1892 FELTON	1974 COMMONWEALTH	.993 PROPORTION
M-6		• •	\
····			1
26401	2588.52	2591.83	
CLO	1892 FELTON	1974 COMMONWEALTH	
1821 GLO	892	974	
-	Ä		

M-5

\* NOTE: THIS DISTANCE APPEARS TO HAVE BEEN MEASURED TO A BOAT SPIKE N. OF M-5 PREVIOUSLY HELD AS THE CORNER BUT NOT USED FOR THE SINGLE PROPORTION CITED IN SWARTS 1974 LCRC PG.34