## 1993 REMONUMENTATION PROGRAM LAND CORNER RECORDATION CERTIFICATE

COMMISSION		uirement of Áct 74, Mich. P.				~	LO.	الد.	A
For corners in		INGTON TOWNSHIP	n. 1370		語	불	93 DEC		ECE
	ocated in:	Corner Code #			200	55 25	0		CEIVED
(County)					:::: :::::::::::::::::::::::::::::::::		U,	اصدا	13 23 23
Public Land Survey     T	10 NR 8 E	М-8			575 575				500
	R				(j.		က္ ယ (၂	5 8	E
2. Property Controlling S T	R R				Ø		33 C		- 686 -
in Section S7	R							1)	<u> </u>
3. Miscellaneous S T	RR		Register	r of De	eds S	tamp &	ß File i	Numbe	).
	at		•			-			
4. Lot No, Recorded Plants 5. Private Claims	at		1 A	ВС	D 1	E F G	H 1	J K	L M
			2	6	5	4	3	2	1
I, JONATHAN M. FIELD	, in a field sur	vey on OCTOBER 19 93	3 -	7	-8	9	10	11	12
do hereby certify that under requirements in lines 1 and 2 above were in conforma	of P.A. 74, Michigan P.	A. of 1970, the corner points mentione		· ·		· · · · · ·			
current manual of survey instructions of the Management or by a decree of a Court of L	ne United States Depa	riment of the interior, Bureau of Lan-	d 6	18	17	16	15	14	13
above were in conformance with the rules Court of Law; established, re-establis	of the Michigan Board	of Land Surveyors or by a Decree of	a '	19	20	21	22	23	24
expressed below:	neo, monumenteo, re	e-monumented, recovered, loding a	9					-:-	
NOTE: Not more than 4 corners,	all in the same tow	n and range, may be recorded	10	30	29	28	27	26	25
on this certificate.			11	31	32	33	34	35	36
A. Description of original monume	at and assessation	andlar subasquant restaration:	13 L				_ Ţ`.	<u> </u>	L
B. Description of corner evidence:	WEST 28.00' 4" E) 192; SURVEY L.54' 0709; SURVEY L.61' 276; SURVEY L.61' found and/or methology for the same of th	LM 7 PG.389-390 - FND 1/2" ROD; 09 PG.441-442 - FND 1/2" ROD; 8" TWIN OAK, N30W 39.16' P- 9 PG.1063-1064 - FND 1/2" RO  d applied in restoring or reestable DD IN CENTER OF GRAVEL ROAD POSITION AS 1969 SURVEY AND	SAME WITS ); S75E 48.1  K 5" OAK D; SAME WIT  shing corner: N-S FND 4 F	AS 19 3' NA 'S AS PREV W	79 LEF IL 14" 1990 F	ACH SU. HICK REI SU. ND MEA	RVEY ORY, RVEY SUREME		
•				C					
·									
M-6 SET STANDARD MONUMENT (5/8 S75°E, 53.66' SET NAIL W/R WEST, 28.28' SET NAIL W/R N20°E, 46.10' SET NAIL W/R N30°W, 39.16' SET NAIL W/R S46°E, 38.79' TOP CENTER O	" ROD W/ BRASS CO EMON TAG IN S. FA EMON TAG ABOVE FO EMON TAG IN NW FA EMON TAG ABOVE FO F PHONE RISER	ACE 16" POPLAR ND NAIL IN N. FACE 6" ELM ACE TWIN 8" OAK ND P-K NAIL IN NE FACE 6" OA	ĸ	ion of t	the cor	JON M.	IATHA FIELI LAND RVEYO No. 37276	)	
Signed by Junatur M7		Date	6-93				L. 154.44.44		
Surveyor's Michigan License No.	37276		FORM APPROVED B	Y MICHIGAI	N STATE 8	OARD OF L		EVISED MA	
		RDD 1			ADAPT	ED FOR W	ORD PROC		

## AdOO



SECTION 24 TION-R8E

				4
26401	2578.62	2571.81	2571.69	2571.37
1821 GLO	1882 TESKEY	1969 FLINI SURVEY 2571.81	1979 LEACH	7 1002 BFT
***************************************	M-	-8	•	
		2640	2578_62	2571 271
		1821 GL0	1882 TESKEY	1000
				¥