1996 REMONUMENTATION PROGRAM

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in Koylton Twp.

Tuscola	Located In:	Corner Code #		2008 2009 2009	VED VED
(County) 1. Public Land Survey	T <u>11NR 11H</u>	E (A-12)			
1. Public Land Sulvey	TR T//\d R/06				
	TR			5 × 5	E CORRE
2. Property Controlling in Section	S IR S TR			٠ ر	
3. Miscellaneous Property in Sec.	S TR S TR		Regist	er of Deeds Stan	np & File Number
,			110910	<u></u>	
4. Lot No, Record	ed Plat		A B	CDEFG	H I J K L M
5. Private Claims			2 - 6	54	3 - 2 - 1 -
Warranth D. Danston	Ma	31 40 0 G de bessehsselste	that under 4 7		10-11-12-
requirements of P A 74 Michigan	P A of 1970, the corner of	ay 11, 1996 do hereby state oints mentioned in lines 1 and 2 about the support of support instance.	we were in _		
Hullard States Department of the In-	terior, Ruteau of Land Mana	the current manual of survey instruc- gement or by a decree of a Court of L e in conformance with the rules of th	.aw and /or 6 18	17-16-	15 14 13
Board of Land Surveyors or by a recovered, found as expressed belo	a Decree of a Court of La	aw; established, re-established, mo	numented,	20 21 -	.22 23 24
NOTE: Not more than 2 come		nd range, may be recorded:	9		
on this certificate.	,		10 30	29 28 -	27 26 25
		·	12 31	32 33	34 35 36
		and/or eubegalient restoration:	13		1
A. Description of original mon					
G.L.O. 1834 Harvey Parke, D.		gust 23, 1882 hn A. Teskey, Cou	nty Surveyor		
Set Quarter Sec.	Post Sec	c. 31 TllN-R11E			
Hemlock 22 N28W Beech 5 S10 1	/2W 3l Per	ake previously se rpetuated by stak			
Corner M-12, Tl1N-R1		accessories			,
		back of form.	. II. talan an armor		
B. Description of corner evidence	ence found and/्र metho	od applied in restoring or reestat	onshing comer.		
Found 1/2" rod ()	oent). Held a	as the best evide	nce of the o	riginal co	rner.
	•				'n
•					:
a B duties of sequences of f	or corner and accessorif	es established to perpetuate loca	iting the position of the	corner:	Ž
		dard monument star			-R10E.
S14°W 107.33' se	et T. C. Remor	n. tag & spike in	NW face T. I	pole stub.	RIOM V
\$88°E 33.20' set	T. C. Remon.	n. tag & spike in . tag & spike in 1	N. face P. po	ole.	
•		atop E. end 12" C	SP.		
Note: This corner	is common with M	I-12, T11N-R1 0E.		********	
,	0000	Q M	A PATE OF	MICHIGAN	
Signed by	XXV!/2		ate KEKNE	TH D	
Signed by Surveyor's Michigan License N	lo23503	4.0	★ LA	TON X	
part of the second	APPRO	VED SHE	SURV	o.	SURVEYORS, JAN. 28, 1971
	11-11-9	6 CONT FORM APPROV	/ED BY MICHIEAN TATE BOX	Silver Control	REVISED MAY 14,1975 REVISED JAN., 1983 REVISED OCT., 1995
F3477 0 0 0000		シハブロ	WAND TO FEE	SIONER	KEAISED OC!" JANS.
H17 2 0 1007					3.0

Aug. 4, 1977
Survey by Robert G. Kay, Land Surveyor #14096, Liber 476-Pages 948 & 949. 1/2" iron.
S20°W 107.15' nail T.P. riser.
West 26.80' nail fence post.
East 21.40' nail fence post.

May 7, 1991

Survey by John A. Milletics, Land Surveyor #25859, Liber 614-Page 1000. No mention of object found or set or accessories.

