	AND COOLED DECORD ATTOM OFFICIAL	Oct 18	19 03	py 19tl		_
LI	BOC 4 PAGESIAN LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970		14 63	111 <b>U</b> T	_	
For	corners in Bloomingdale Township	Ma.	1.00	mille	7.00	
	Van Buren County Located In: Corner Code ##	4 /(W	VAN BUREN	ONCX+	) (	
	1-7				~	
1.	Public Land Survey  T 1 S R 14 W R T T R R R R R R R R R R R R R R R R				0101 10SURVEY	
	SW Cor Sec 14				E SC	
	T R				<del>~</del>	
	Property Controlling         S T R           in Section         S T R				070	
		gister of Dee	ds Stam	p & File N	lumber	
	Property in Sec. S T R	<del>-</del>		·	<del></del>	
4	Lot No, Recorded Plat		2	в н і	1 K 12	
5.	Private Claims			ŢŢŢ	<del></del>	
		3 3	54-	3		
	G	4 7-	e 8	10	_111	
	Donald R. Gilchrist September 26, 191994	5				
n li	ereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned nes 1 and 2 above were in conformance with regulations and rules therefore as required in the	6 13	17-16	15-	-14	3
Curr Mar	ent manual of survey instructions of the United States Department of the Interior, Bureau of Land agement or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5	8 10		1 1	12	4
abo	ye were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a	9	1			
	rt of Law; established, re-established, monumented, re-monumented, recovered, found as ressed below:	10 30	2928	27-	_2 <del>6</del> 2	5
NO	TE: Not more than 4 corners, all in the same town and range, may be recorded	11	╁╁╅	+++		
	on this certificate.	12 31	32 - 33	34	35 -3	5 <u> </u>
A.	Description of original monument and accessories and/or subsequent restoration:		_			
	Government - set corner post - 16" beech N 67° E 27	lks; 12"	beec	h N73	• W	
	15 lks. W.V. Ackley - 4/2/1909 - Sec 14 - SW Cor (4)? stone;	16" Map	- S	23° E	103	
	1ks: S 1/4 post 20.01 1/2 ch to 1/8 stone; 20.01 1/2	ch to S	W Sec	: Cor;	Sec	
	Cor 25.02 ch E of 1/4 Pt; W 1/4 Pt 20.02 1/2 Ch to 1,	/8 Cor;	20.02	1/2	Cn to	
	Sw Sec Cor. T.A. Smith - 6/30/1923 - Fd pointed stone; 8" map S !	55° E 70	.94 t	o cen	; 2"	
	map - S 40° E 44.3' to cen; 24" map S 23° E 68.9' to	cen; 10	" cor	fen	post	
	S 50° W 43.7' to cen. (Continued on back of Certificat	:e)				
В.	Description of corner evidence found and/or method applied in restoring or reestablishing	corner:				
	Found Harrison Marker in Monument Box.			-		
		atified by Peer dance with P.A.		100	£	
		n Buren County	-			
	••	D. R.A.	•			
	Date _d	J. K. A.	10/18/	79		
				-		
Э.	Description of monument for corner and accessories established to perpetuate locating th	ne position of	the corr	ner:		
	Harrison Standard Monument in Monument Box over stor			P Pol		
	32.07'; nail in 30" maple S 45° E 69.70'; nail in 36 Approved at 10/24/92 meeting of Van Buren County Peet	" maple	S 25°	P E 67	.53'.	
	Fd paved over in field check on 9/26/94 by D.R. Gilcl	hrist, C	lo . Sur	veyor	•	
	Re-approved at the 10/5/94 Van Buren County Peer Grounds	up Meeti	ng ar	ıd is		
	accepted as a careful and faithful perpetuation of the Original Government Corner.	ne posit	LON C		·	
				TE OF	MICHIGA	L.
	_		1	·	To the	. 4
		7	1:/	GILCH	IRIST	*



## TIMER 4 PAGE 165

## Continued from front of Certificate

A. Mitchell - 9/28/92 - found stone - intersected distances from N 1/4 and W 1/4 on T.A. Smith survey and dug for stone. Found pointed stone approx 2' deep at that location. Set monument box and standard monument over stone. Found Harrison Marker in mon box.