LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN-:	CORNER CODE NUMBER	
1. PUBLIC LAND SUR	VEY 14 T. 4 S., R. 13 V.	<u> </u>	
2. PROPERTY CONTRING IN SECT	OLL- TION-14 ,T. 4 S., R. 13 V.	J-5	
	TION, T N E E W.		
	, RECORDED PLAT		
5. PRIVATE CLAIMS _	·		REGISTER OF DEEDS STAMP AND FILING NUMBER
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on Scot 13 1923, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on Scot 13 1923, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:			
A. Description of original monument and accessories and/or subsequent restoration:			
B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:			
Recovered Replaced w	34" I RON Pipe 2" 2 AA Cons. Non amont Co	Below Ground (by W.Q.SMITH)
C. Description of m	onument for corner and accessories	established to perpetuate loc	ating the position of the corner:
4" Dia. Con.	to Mark		·
N. 72° W.	9.95' Power Pole		
	28.39' 5" OAK		
N. 85° E.	62.20' 6" Willow		
N. 61° E.	62.20 7" Elm		
South	46.55 Cone. Mon.		
SIGNED BY		DATE	· · · · · · · · · · · · · · · · · · ·
SURVEYOR'S MICHI	GAN REGISTRATION NO.		(SEAL)
FOR STATE AND U	NITED STATES AGENCIES:		
SIGNED BY	CHIEF OF SURVEY PARTY	DATE	
APPROVED AND SIG		AND SURVEYOR DATE	
			(SEAL)