LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

1. PUBLIC LAND SURVEY AT T. 4 S. R. 13 1 1-5 2. PROPERTY CONTROLL. 14 T. 4 S. R. 13 1 1-5 3. MISCELLANGEOUS T. S. R. E. 15 3. MISCELLANGEOUS T. S. R. E. 15 4. LOT NO. RECORDED PLAT 5. PRIVATE CLAIMS 1. D. Scalt do hereby certify that under requirements of P. A. 74, Michigan P. A. of 1970, the corner points gentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were died survey on private of a corner points gentioned in lines 3 and rules therefore as required in the current material as expressed below and in conformance with regulations and rules therefore as required in the current material as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law: 1. 19 25 (cond., ecorrect, learned, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law: A. Deacription of original monument and accessories and/or subsequent restoration: B. Deacription of original monument and accessories and/or subsequent restoration: B. Deacription of corner evidence found and/or method applied in teatoring or re-establishing corner: 3. I RON Poc Flush with Blacktop Rond Recovered uscing Notes from T.A. Smith of Row Row, Michigan No. 12 Control of Registration for Land Surveyors or, by a Decree of a Court of Registration of	FOR CORNERS OF -:	LOCATED IN-:	CORNER CODE NUMBER		
3. MISCELLANDOUS N. RECORDED PLAT 4. LOT NO	1. PUBLIC LAND SURVEY 14	T. 4 S., R. 15 V.			
4. LOT NO	2. PROPERTY CONTROLL-	,T. <u>4</u> S., R. <u>13</u> V.	1-5		
S. PRIVATE CLAIMS Above Context points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field aurey on 22 3 1923 established, re-established, monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the corner points mentioned in lines 1, and 5 above were, in a field survey on 1923 found, recovered or court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 1923 found, recovered, restored, established or reseablished as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law: A. Description of original monument and accessories and/or subsequent restoration: B. Description of original monument and accessories and/or subsequent restoration: B. Description of corner evidence found and/or method applied in restoring or re-establishing corner: 34 Tron Poc Flush with Blacktop Rond Recovered useing Notes from T.H. Smith of Pawlaw, Michigan C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: 34 Tron Poc flush with Blacktop Rond N. 16 45 W. 117.90 Power Pole N. 81-00 E. 117.50 Bweer Pole N. 81-00 E. 117.50 Bweer Pole North 3.11 N. Edge Blacktop South 16.0 S. Edge Blacktop South 16.0 S. Edge Blacktop Signed By DATE SURVEYOR'S MICHIGAN REGISTRATION NO. 12 029 [1824.] DATE APPROVED AND SIGNED BY DATE		<u> </u>			
A Description of corner evidence found and/or method applied in restoring or re-establishing corner: 3. Trans Pac Flush with Blacktop Rond Recovered Useing Montes found and accessories established to perpetuate locating the position of the corner: 3. Trans Pac Flush with Blacktop Rond C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: 3. Trans Pac flush with Blacktop Rond C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: 3. Trans Pac flush with Blacktop Rond Recovered useing Notes from T.A. Smith of Rond Recovered useing Notes flush with Blacktop Rond Recovered useing Notes flush with Blacktop Rond Recovered useing Notes flush with Blacktop Rond N. 19-45 W. 117.90 Ruck Poic N. 19-45 W. 117.90 Ruck Poic North 3.00 Notes flush with Blacktop Rond N. 19-40 E. 117.50 flush with Blacktop Rond North 3.00 Notes flush with Blacktop Rond North 3.00 Notes flush with Blacktop Rond North 4.00 S. Edge Black top Mathematics for North 18 Nort	4. LOT NO , RECO	RDED PLAT			
the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were; in a field survey on 10 20 3 1923 established, re-established, monumented, re-monumented, re-monument of survey instructions of the lines of	5. PRIVATE CLAIMS				
B. Description of corner evidence found and/or method applied in restoring or re-establishing corner: 34 IRON Pipe Flush with Blacktop Road Recovered useing Notes from T.A. Smith of Paw Paw, Michigan C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: 34 IRON Pipe flush with Blacktop Road N. 26-45 W. 117.80 Power Pole N. 84-00 E. 117.80 Power Pole North 3.0 N. Edge Blacktop South 16.0 S. Edge Blacktop South 16.0 S. Edge Blacktop South 16.0 S. Edge Blacktop Massurements to Nation in S. Side of 1865 SIGNED BY DATE APPROVED AND SIGNED BY WALLEST AMERICAN MAINTERN AND MANUFACE AND MAINTEN LAND MANUFACE AND MAINTEN LAND MANUFACE AND DATE APPROVED AND SIGNED BY WALLEST AMERICAN MAINTEN LAND MANUFACE AND DATE DATE	the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram – over) were, in a field survey on 1923 established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 1923 found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of				
Recovered useing Notes from T.A. Smith of Paw Paw, Michigan C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: 34" Iron Pipe flush with Black typ Road N. 96-45" W. 117.90" Power Poie North 3.0" N. Edge Black typ South 16.0" S. Edge Black typ Measurements to Nails in S. Side of 13/25 SIGNED BY DATE 2-3-73 SURVEYOR'S MICHIGAN REGISTRATION NO. 12 029 OMET DATE OMET OF BURNEY PARTY APPROVED AND SIGNED BY NICHIAM REGISTRATION DATE DATE DATE DATE DATE	A. Description of original monument and accessories and/or subsequent restoration:				
Recovered useing Notes from T.A. Smith of Paw Paw, Michigan C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: 34" Iron Pipe flush with Black typ Road N. 96-45" W. 117.90" Power Poie North 3.0" N. Edge Black typ South 16.0" S. Edge Black typ Measurements to Nails in S. Side of 13/25 SIGNED BY DATE 2-3-73 SURVEYOR'S MICHIGAN REGISTRATION NO. 12 029 OMET DATE OMET OF BURNEY PARTY APPROVED AND SIGNED BY NICHIAM REGISTRATION DATE DATE DATE DATE DATE					
C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: 34" IRON Pipe flush with Black top Road N. 96-45" W. 117.90" Pawer Pole N. 81-00 E. 117.50 Pawer Pole North 3.0" N. Edge Black top South 16.0" S. Edge Black top The surrements to Nails in S. Side of 18/es SIGNED BY DATE SURVEYOR'S MICHIGAN REGISTRATION NO. 12 029 TORSTATE AND UNITED STATES AGENCIES: SIGNED BY DATE CHIEF OF SURVEY PARTY APPROVED AND SIGNED BY MICHIGAN REGISTRATION DATE	34 IRON Pipe Flush with Blacktop Road				
74" IRON Pipe flush with Black top Road N. 96-45' W. 117.90' Power Pole N. 81-00 E. 117.50 Power Pole North 3.0' N. Edge Black top South 16.0' S. Edge Black top Measurements to Nails in S. Side of 13/25 SIGNED BY DATE SURVEYOR'S MICHIGAN REGISTRATION NO. 12 029 CHIEF OF SURVEY PARTY APPROVED AND SIGNED BY MICHIGAN REGISTRED LAND SURVEYOR DATE DATE DATE DATE					
N. 81-00 E. 1/7.50 Fower Tole North 3.0' N. Edge Black top South 16.0' S. Edge Black top Measurements to Nails in S. Side of Blas SIGNED BY DATE SURVEYOR'S MICHIGAN REGISTRATION NO. 12 029 (SEAL) FOR STATE AND UNITED STATES AGENCIES: SIGNED BY CHIEF OF SURVEY PARTY APPROVED AND SIGNED BY MICHIGAN REGISTRATIV DATE MICHIGAN REGISTRATIVE DATE				ating the position of the corner:	
SIGNED BY DATE SURVEYOR'S MICHIGAN REGISTRATION NO. 12 029 FOR STATE AND UNITED STATES AGENCIES: SIGNED BY CHIEF OF SURVEY PARTY APPROVED AND SIGNED BY MICHIGAN REGISTERED LAND SURVEYOR DATE DATE DATE	N.76-45 W. 11 N. 81-00 E. 117 North 3 South 16	17.90' Power Pole .50 Power Pole .1' N. Edge! O' S. Edge!	l Black top Black top		
SURVEYOR'S MICHIGAN REGISTRATION NO	Measurements	to NAILS IN S. Side .	+ 13/05	-3-73	
FOR STATE AND UNITED STATES AGENCIES: SIGNED BY		ISTRATION NO. 12			
APPROVED AND SIGNED BY DATE DATE					
	SIGNED BY	CHIEF OF SURVEY PARTY	DATE		
	APPROVED AND SIGNED BY	MICHIGAN REGISTERED LA	IND SURVEYOR DATE		