SURVEY & REMONUMENTATION

APR 2 5 1995

Signed by Kenneth S. Wilkerson Surveyor's Michigan License No. 21584

Irchard, Hiltz and McCliment, Inc. 34935 Schoolcraft Road Livonia, MI 48150

RC 1438

LI27794PA302

LAND CORNER RECORDATION CERTIFICATE

CO	MN	11S	SI	ON
\sim	16114		•	~ , , ,

Filing Requirement of Act 74, Mich. P.A. 1970

-		M-01 Page 1
For corners in		·
Wayne	Located in: Sumpter Corner Coc	ie
County		
Public Land Survey	T 4 S R 8 E M-01	Compliance with
	T R	ACT 345, P.A. 1990
	TR	APPROVED ON: 12/9/94 7/CAU
2. Property Controlling S	TR	WAYNE COUNTY REMONUMENTATION
in Section S	TR	PEER GROUP COMMITTEE
3. Miscellaneous S	TR	
Property in Sec. S	TR	Register of Deeds Stamp and File Number
4. Lot No, Recorded Plat		· · · · · · · · · · · · · · · · · · ·
5. Private Claims	•	A B C D E F G H I J K L
		2 - 6 5 4 3 2 1
t to lid C will	141 7/1004	3
I. Kenneth S. Wilkerson in a field sur	vey on	4 7 8 9 10 11 12
do hereby certify that under requirement mentioned in lines 1 and 2 above were	is of P.A. 74, Michigan P.A. of 1970, the	day the entree
required in the current manual of survey	in comormance with regulations and ru	185 INSTRICTS 6 - 18 - 17 - 16 - 15 - 14 - 13
Interior, Bureau of Land Management.	or by a decree of a Court of Law and/o	r that the corner
points mentioned in lines 3, 4 and 5 abo	ove were in conformance with the rules	of the Michigan 8 - 19 - 20 - 21 - 22 - 23 - 24
Board of Land Surveyors or by a Decre	e of a Court of Law, established, re-est	ablished, P
monumented, re-monumented, recover	ed, found as expressed below.	10 - 30 - 29 - 28 - 27 - 26 - 25
NOTE: Not more than 4 corners, all 1	n the same town and range, may be	11
recorded on this certificate.		12 -31 - 32 - 33 - 34 - 35 - 36
		13
A. Description of original monument and	d accessories and/or subsequent rosto	
	accessories and/or subsequent resto	
•	T. I.	G.L.O. Set post
24" W. OAK N 60 W 1		
8" ASH S 75 E 14 LINI	(3 (9.24)	
(Witnesses Continued on Back)	•
B. Description of corner evidence found	and or mathed applied by seat-size as	an and all the later and an
	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·
HAND HELD G.P.S. UNIT.	LOCATED IN FLOOD PLAIN, OF	HURON RIVER, LOCATED BY
C. Description of monument for corner a	and accessories established to perpetu	ate locating the position of the corner:
12/17/1994 Wilkerson	21584 OHM	Remon
INTERSECTION OF E	ENCES TO W., E., & S. & 20' S OF	
SET W.C.R. WASHER	ON CORNER	\$ 16.00 MISCELLANEOUS RECORDING
	E 14" BASEWOOD N70E 18.66'	21 DEC 94 3:19 P.W. TECHTS # 930
	E 10" MAPLE S5W 26.46'	TO THE PARTY OF TH
8 SET P.K. NAIL 13" SC	YAMORE \$80W 10.36'	addition of Analis will seed the because in
9 SET P.K. NAIL W. FAC	CE 6" ELM N20W 21.48'	पुष्पात राष्ट्राभाव स्थाप
,		
We conclude that after careful study of t	he record documentation and field ob-	ervations that this corner in training
he best available evidence of the position	n of the original corner.	orvations, that this corner beseccopted as
	/_//:	Call Control of Call

L127794PA303

M-01 Page 2

 Λ (Continued) Description of original monument and accessories and/or subsequent restorations:

01/01/1930

Wayne Co. Bureau of

Mon. set in place of iron

Bureau of Taxation

- 1 WEST 217 TO HURON RIVER
- 2 18" ELM N.W. 66.07'
- 3 MON NORTH 1028'
- 4 14" ELDER N.E. 58.32'
- 5 16" WALNUT EASTERLY 56.99'