LAND CORNER RECORDATION CERTIFICATE FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

	FOR CORNERS OF -:			
	t. PUBLIC LAND SURVEY	T. 21 N. R. 12	w. K−13; L−13; M−13	
	2. PROPERTY CONTROLL- ING IN SECTION	,T S., R	E. W.	
	3. MISCELLANEOUS PROPERTY IN SECTION	,T S., R.	E	
	4. LOT NO , RECO	RDED PLAT		
	5, PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND FILING NUMBER
	the corner points mentioned in lin re-established, monumented, re-n and rules therefore as required in Bureau of Land Management or l and 5 above were, in a field surve	es 1 and 2 above were, is commented, recovered to the current manual of soly a decree of a court of you	n a field survey onJUNE r restored as expressed below urvey instructions of the Unite law. Furthermore, that the co, 19, found, recovered,	nts of P.A. 74, Michigan P.A. of 1970, 17 , 19.81, established, and in conformance with regulations ed States Department of the Interior, orner points mentioned in lines 3, 4 restored, established or re-established egistration for Land Surveyors or, by a
	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	KAKKXAKKKKKKKKKKKKK	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	
!!! !	MAPLE N85°E 7	3.391		·
13 13	LINE OF T21N-R12W. UFD. AND ACCEPTED STD. USED TWO ROBT. GRIFFINE FD. AND ACCEPTED U.S. R12W AND SEC. 31, T21	F.S. CONC. MONUMENTSED THREE ROBT. GREWEXFORD COUNTY MONUMENTS. WITS. F.S. BRASS CAP CONTINUES. ON SECOND	NT FOR SEC. CORNER CORRESTED U.S.F.S. WITS. DNUMENT FOR THE S 1/4 NC. MONUMENT FOR SEC. CORRECTION LINE.	CORNER OF SEC. 36, T21N-R12W CORNER COMMON TO SEC. 36,T21 DRNER MONUMENT FALLS AT OLD
13	FD. AND ACCEPTED U.S.I LINE OF T21N-R12W. U FD. AND ACCEPTED STD. USED TWO ROBT. GRIFFIN FD. AND ACCEPTED U.S.I	F.S. CONC. MONUMENTSED THREE ROBT. GREWEXFORD COUNTY MONUMENTS. WITS. F.S. BRASS CAP CONTINUES. ON SECOND	NT FOR SEC. CORNER CORRESTED U.S.F.S. WITS. DNUMENT FOR THE S 1/4 NC. MONUMENT FOR SEC. CORRECTION LINE.	CORNER OF SEC. 36, T21N-R12W CORNER COMMON TO SEC. 36,T21 DRNER MONUMENT FALLS AT OLD
13 13 13	FD. AND ACCEPTED U.S. LINE OF T21N-R12W. UFD. AND ACCEPTED STD. USED TWO ROBT. GRIFF!! FD. AND ACCEPTED U.S. R12W AND SEC. 31, T21! FENCE CORNER, ON GROUNCE. Description of monument for	F.S. CONC. MONUMER SED THREE ROBT. GR WEXFORD COUNTY MONULUS.F.S. WITS. F.S. BRASS CAP COMPAND; FENCE'S E-W-N CORNER and accessories es	NT FOR SEC. CORNER CORRESTING U.S.F.S. WITS. DNUMENT FOR THE S 1/4 NC. MONUMENT FOR SEC. CORRECTION LINE. CO. USED THREE ROBT. Gratablished to perpetuate locating	CORNER OF SEC. 36, T21N-R12W CORNER COMMON TO SEC. 36,T21 DRNER MONUMENT FALLS AT OLD RIFFIN U.S.F.S. WITS.
13 13 13	FD. AND ACCEPTED U.S. LINE OF T21N-R12W. UFD. AND ACCEPTED STD. USED TWO ROBT. GRIFF!! FD. AND ACCEPTED U.S. R12W AND SEC. 31, T21! FENCE CORNER, ON GROUNCE. Description of monument for	F.S. CONC. MONUMER SED THREE ROBT. GR WEXFORD COUNTY MONULUS.F.S. WITS. F.S. BRASS CAP COMPAND; FENCE'S E-W-N CORNER and accessories es	NT FOR SEC. CORNER CORRESTING U.S.F.S. WITS. DNUMENT FOR THE S 1/4 NC. MONUMENT FOR SEC. CORRECTION LINE. CO. USED THREE ROBT. Gratablished to perpetuate locating	CORNER OF SEC. 36, T21N-R12W CORNER COMMON TO SEC. 36,T21 DRNER MONUMENT FALLS AT OLD RIFFIN U.S.F.S. WITS. 4 the position of the corner:
13 13 13 :: '	FD. AND ACCEPTED U.S.I LINE OF T21N-R12W. U FD. AND ACCEPTED STD. USED TWO ROBT. GRIFFII FD. AND ACCEPTED U.S.I R12W AND SEC. 31, T21I FENCE CORNER, ON GROUP C. Description of monument for K-13 5"X5" BRASS CAP CONC MOR W.OAK N20°E B.CHERRY N55°E 11" MAPLE N50°W 4"X4" SQ.POST DUE N	F.S. CONC. MONUMER SED THREE ROBT. GR WEXFORD COUNTY MONULOS.F.S. WITS. F.S. BRASS CAP COR N-RIW. ON SECOND ND; FENCE'S E-W-N CORNER and accessories es N; BURIED 10". 91.55' 81.25' 59.36'	NT FOR SEC. CORNER CORRESTING U.S.F.S. WITS. DNUMENT FOR THE S 1/4 NC. MONUMENT FOR SEC. CORRECTION LINE. CO. USED THREE ROBT. Gratablished to perpetuate locating	CORNER OF SEC. 36, T21N-R12W CORNER COMMON TO SEC. 36,T21 DRNER MONUMENT FALLS AT OLD RIFFIN U.S.F.S. WITS. 4 the position of the corner:
13 13 13 13	FD. AND ACCEPTED U.S. LINE OF T21N-R12W. UFD. AND ACCEPTED STD. USED TWO ROBT. GRIFFITH FD. AND ACCEPTED U.S. R12W AND SEC. 31, T21FENCE CORNER, ON GROUP C. Description of monument for K-13 5"X5" BRASS CAP CONC MONUMENT OF MACK N20°E B.CHERRY N55°E 11" MAPLE N50°W 4"X4" SQ.POST DUE N	F.S. CONC. MONUMER SED THREE ROBT. GR WEXFORD COUNTY MONULOUS.F.S. WITS. F.S. BRASS CAP COR N-R1W. ON SECOND ND; FENCE'S E-W-N CORNER and accessories es N; BURIED 10". 91.55' 81.25' 59.36' 32' 2'±	NT FOR SEC. CORNER CORRESTIN U.S.F.S. WITS. ONUMENT FOR THE S 1/4 NC. MONUMENT FOR SEC. CORRECTION LINE. CO. USED THREE ROBT. GR tablished to perpetuate locating L-13 FD. WEXFORD COUNTY 11" R. PINE S500 10" R. PINE S400 FD 4"X4" POST DUE	CORNER OF SEC. 36, T21N-R12V CORNER COMMON TO SEC. 36,T21 DRNER MONUMENT FALLS AT OLD RIFFIN U.S.F.S. WITS. 4 the position of the corner:
13 13 13 	FD. AND ACCEPTED U.S. LINE OF T21N-R12W. UFD. AND ACCEPTED STD. USED TWO ROBT. GRIFFII FD. AND ACCEPTED U.S. R12W AND SEC. 31, T21I FENCE CORNER, ON GROUP C. Description of monument for K-13 5"X5" BRASS CAP CONC MORNOUS NOAK N20°E B.CHERRY N55°E 11" MAPLE N50°W 4"X4" SQ.POST DUE NEW DIRT ROAD SOUTH	F.S. CONC. MONUMER SED THREE ROBT. GR WEXFORD COUNTY MONULS.F.S. WITS. F.S. BRASS CAP COMPAND; FENCE'S E-W-N COTHER and accessories es N; BURIED 10". 91.55' 81.25' 59.36' 32' 2'±	NT FOR SEC. CORNER CORRESTIN U.S.F.S. WITS. DNUMENT FOR THE S 1/4 NC. MONUMENT FOR SEC. CORRECTION LINE. CO. USED THREE ROBT. GRADISHED to perpetuate locating L-13 FD. WEXFORD COUNTY 11" R. PINE S500 10" R. PINE S400 FD 4"X4" POST DUE	CORNER OF SEC. 36, T21N-R12W CORNER COMMON TO SEC. 36,T21 DRNER MONUMENT FALLS AT OLD RIFFIN U.S.F.S. WITS. 4 the position of the corner:
13 13 13 	FD. AND ACCEPTED U.S. LINE OF T21N-R12W. UFD. AND ACCEPTED STD. USED TWO ROBT. GRIFFINGE. AND ACCEPTED U.S. R12W AND SEC. 31, T21N FENCE CORNER, ON GROUND C. Description of monument for K-13 5"X5" BRASS CAP CONC MONOR NOAK N20°E B.CHERRY N55°E 11" MAPLE N50°W 4"X4" SQ.POST DUE NEW DIRT ROAD SOUTH SIGNED BY TO SUTT SECRET STATE AND UNITED ST	F.S. CONC. MONUMER SED THREE ROBT. GR WEXFORD COUNTY MON U.S.F.S. WITS. F.S. BRASS CAP COMPAND; FENCE'S E-W-N corner and accessories es N; BURIED 10". 91.55' 81.25' 59.36' 32' 2'± Out 04-06 ATES AGENCIES:	NT FOR SEC. CORNER CORRESTIN U.S.F.S. WITS. DNUMENT FOR THE S 1/4 NC. MONUMENT FOR SEC. CORRECTION LINE. CO. USED THREE ROBT. GR tablished to perpetuate locating L-13 FD. WEXFORD COUNTY 11" R. PINE S500 10" R. PINE S400 FD 4"X4" POST DUE	CORNER OF SEC. 36, T21N-R12W CORNER COMMON TO SEC. 36, T21D CORNER MONUMENT FALLS AT OLD RIFFIN U.S.F.S. WITS. The position of the corner: MON; BURIED 1" IN RD INTERSE PE 61.33' PW 46.51' N 33 1/2' CARL F. ROSER AND SURVEYOR NO. 12028- LAND L
13 13 13 	FD. AND ACCEPTED U.S. LINE OF T21N-R12W. UFD. AND ACCEPTED STD. USED TWO ROBT. GRIFFINGE. AND ACCEPTED U.S. R12W AND SEC. 31, T21N FENCE CORNER, ON GROUND C. Description of monument for K-13 5"X5" BRASS CAP CONC MONOR NOAK N20°E B.CHERRY N55°E 11" MAPLE N50°W 4"X4" SQ.POST DUE NEW DIRT ROAD SOUTH SIGNED BY TO SUTT SECRET STATE AND UNITED ST	F.S. CONC. MONUMER SED THREE ROBT. GR WEXFORD COUNTY MON U.S.F.S. WITS. F.S. BRASS CAP COMPAND; FENCE'S E-W-N corner and accessories es N; BURIED 10". 91.55' 81.25' 59.36' 32' 2'± Out 04-06 ATES AGENCIES:	NT FOR SEC. CORNER CORRESTIN U.S.F.S. WITS. DNUMENT FOR THE S 1/4 NC. MONUMENT FOR SEC. CORRECTION LINE. CO. USED THREE ROBT. GR tablished to perpetuate locating L-13 FD. WEXFORD COUNTY 11" R. PINE S500 10" R. PINE S400 FD 4"X4" POST DUE	CORNER OF SEC. 36, T21N-R12W CORNER COMMON TO SEC. 36,T21 DRNER MONUMENT FALLS AT OLD RIFFIN U.S.F.S. WITS.