LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. _____ N. S., R. _____ E. W.	_____
2. PROPERTY CONTROLLING IN SECTION 12	,T. 22 N. S., R. 9 E. W.	10;11;12
3. MISCELLANEOUS PROPERTY IN SECTION _____	,T. _____ N. S., R. _____ E. W.	_____

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on January 9, 1986, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. (Continued):

12

Drove 5/8"x34" rerod w/RLS cap & set cedar post w/loc tag

8" Red Pine	N15°W	12.1'
7" Red Oak	N50°E	34.6'
3" White Oak	S40°E	39.6'
22" Red Oak	S20°W	5.6'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

10 - Drove 5/8" x 34" rerod for NW corner of SW¼ of SW¼ of Section 12.

11 - Drove 5/8" x 34" rerod for NE corner of SW¼ of SW¼ of Section 12.

12 - Drove 5/8" x 34" rerod for NE corner of SE¼ of SW¼ of Section 12.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

10

Drove 5/8" x 34" rerod w/RLS cap

8" Black Cherry (clp 2)	N10°W	27.5'
15" Maple	S60°E	38.9'
24" Red Oak (clp 2)	S05°W	23.1'
Ctr. E-W dirt rd.	Due N	4'
Ctr. E-W R.R. tracks	Due S	139'
Set ced. post w/loc tag	Due N	33'
Fd 3/4" pipe	S46°E	10.8'

11

Drove 5/8" x 34" rerod w/RLS cap & set cedar post w/loc tag

2" White Oak	N45°W	21.8'
3" White Oak	N05°E	24.0'
3" Red Oak	S40°E	35.3'
3" Red Oak	S10°W	22.9'
3/8" pipe	N89°52'W	164.74'

SIGNED BY Carl F. Roser 01-24-86 DATE _____

STATE OF MICHIGAN CARL F. ROSER (SEAL) LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

WEXFORD COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET